

# PPE APPAREL

Part # CO-224T

Coverall

Fabric: Microporous Film/SMS

Weight: 2.8 oz/ 85 gsm

Sealed taped Seams

Wrist: Elastic

Ankle: Attached non skid boot

Color: White

Fold down collar

Sizes: Small to 6XL

Packaging:

25 per inner carton

Physical Property	Test Method	Result
Basis Weight		2.11 oz/sq.yd.
Strip Tensile (MD)	ASTM D5035	12.4 lbs
Strip Tensile (XD)	ASTM D5035	10.0 lbs
Tensile Strength (MD)	ASTM D5034	32.4 lbs
Tensile Strength (XD)	ASTM D5034	32.6 lbs.
Air Permeability	ASTM D737	>0.562 cfm/ft2
MVTR		1489
Hydrostatic Water Resistance	ASTM D751	>127 cm
Particle Holdout	>1.0 microns	99.00%

Microporous film is laminated for excellent fluid resistance and holdout. It passes blood borne pathogen 1670 and viral penetration 1671 tests for use in containment areas. Spun bounded Polypropylene reinforced by a SMS scrim core for strength and flexibility.

## LSP

Life Science Products  
124 Speer Rd  
Chestertown, MD 21620

1-800-638-9874  
Fax: 410-778-2476  
e-mail: [www.FGD@lspinc.com](mailto:www.FGD@lspinc.com)

Website- [www.lspinc.com](http://www.lspinc.com)