

MATERIAL SAFETY DATA SHEET

SECTION 1 IDENTIFICATION

CLIFFORD W. ESTES CO., INC
40 VREELAND AVE STE 104
TOTOWA, NJ 07512

DATE: JANUARY 2005
PHONE: 973.890.1515

PRODUCT BRAND NAME: PERMACOLOR SURFACE AGGREGATES, REGULAR AND HP

PRODUCT IDENTIFICATION : BROADCAST(MED.&FINE), TROWEL-RITE (REGULAR AND SUPER), VARIOUS COLORS

CHEMICAL NAME: SILICON DIOXIDE (SIO2)

DEPARTMENT OF TRANSPORTATION: SAND, GRAVEL, NOIBN

CHEMICAL FAMILY: SILICA SAND

COLOR: TYPICAL COLORS

SECTION II HAZARDOUS INGREDIENTS

CHEMICAL NAME	% WT	CAS#	OSHA (PEL)	ACGIH (TLV)
SILICA SAND	94	14808-60-7		.1MG/M3
RESIN	4.95	NON-HAZARDOUS PROPRIETARY	N/A	N/A
TIO2	0.99	13463-67-7		
COLORANTS ORGANIC AND INORGANIC	0.06	NON-HAZARDOUS		

* Special Statement regarding Hazardous ingredients:

Although these products are composed primarily of Silica Sand (SIO2), and such sand is potentially a source for respirable dust, the sand particles are thoroughly encapsulated in a coating which captures all dust and should, under normal circumstances, prevent any normal release of silica dust to the workplace. See page two, Section VIII for further information on handling.

SECTION III PHYSICAL DATA

BOILING POINT: NONE
VAPOR PRESSURE: NONE
VAPOR DENSITY: NONE
% VOLATILES :<1%
APPEARANCE: SAND OR AGGREGATE, TYPICAL COLORS

SPECIFIC GRAVITY: 2.65
PH: INERT
EVAPORATION RATE: N/A
SOLUBILITY IN WATER: INSOLUBLE

HIMS RATINGS

HEALTH	0*
FLAMABILITY	0
REACTIVITY	0

*REFER TO SPECIAL STATEMENT ABOVE

SECTION IV FIRE AND EXPLOSION HAZARD

FLASH POINT: NON-FLAMMABLE

FLAMMABLE LIMITS: LEL- N/A , UEL - N/A

UNUSUAL FIRE AND EXPLOSION HAZARDS: Products of combustion may include irritating gases.

SECTION V HEALTH AND SAFETY

THRESHOLD LIMIT VALUE: (SEE PAGE ONE)

EFFECTS OF OVER EXPOSURE: Prolonged inhalation of mineral dust may cause delayed lung injury.

EMERGENCY AND FIRST AID PROCEDURES: - EYES, Remove in the same manner as one would remove any foreign particle.

SECTION VI REACTIVITY DATA

STABILITY: Stable

INCOMPATIBILITY: Dissolves in hydrofluoric acid

CONDITIONS TO AVOID: None Known

SECTION VII SPILL/LEAK PROCEDURES

1. Clean up using dustless procedures. Use water and/or vacuum.
2. WASTE DISPOSAL: Dispose using locally approved waste disposal sites.

SECTION VIII SPECIAL PROTECTION

Use of this product under normal and recommended conditions and specifications will pose no known hazards. However, if surfaces using this product are subjected to sanding or grinding as might occur for maintenance purposes, and such treatment produces respirable dust, then proper ventilation and breathing apparatus should be used. Under such conditions, NIOSH-BOM approved respirators should be worn.

GLOVES: Optional

EYE PROTECTION: Full eye zone goggles should be worn.

SECTION IX SPECIAL PRECAUTIONS

1. USE DUSTLESS PROCEDURES DURING HANDLING, STORAGE, AND CLEAN-UP
2. PRACTICE GOOD HOUSEKEEPING. MAINTAIN VENTILATION. POST WARNING TO EMPLOYEES WHERE PRODUCT IS USED, STORED, AND HANDLED.