

UTEK EPQ Flooring System		
Proper Name	Use within System	Name on General MSDS List
101 Resin (SR 101 and SH101)	Body matrix for Aggregate build coat(s)	SR 101 and SH101
Resin 405	Chemical Resistant Epoxy Hardener	CRH 405
UTEK Parts A,B and C	Flooring Resin and Flake Base	T TEK A, B and C
UTEK Color Concentrate	Color	UTEK Color Concentrate
Estes Sand	Aggregate and System Color	Chips

UTEK EP-Q Healthcare Flooring

1. Product Description

Basic use

U-Tek flooring systems are developed to provide moisture tolerant flooring options while incorporating functional flooring resins for chemical resistance, skid resistance and thermal relief. The aliphatic urethane cement base floor with the EP-Q wear course upper system is excellent for use in hygienic facilities requiring stringent cleaning protocols such as OR Suites and areas that are subject to substrate moisture, high impact, chemical resistance and thermal changes. U-Tek EP-Q is highly recommended for wet and wash down areas such as Kitchens.

EP-Q flooring is a hybrid flooring system composed of urethane and epoxy resins using quartz broadcast for texture and color. *U-Tek* EP-Q is composed of LOW or NO VOC resins and as such is LEED compliant. The seal coat is chemical resistant epoxy.

U-Tek systems can be installed over a sloping slab or they may be used to slope and enhance the flow of water to the drain(s). Sloping is recommended in all wet areas since floors that are immersed under constantly ponding water and chemicals tend to deteriorate faster than flooring under alternate wet/dry conditions. Unless otherwise specified, *U-Tek* EP-Q will follow the contour(s) of the existing substrate and can not be used as a stand alone system to correct such problems.

As with any flooring system, environmental conditions surrounding the installation are important. Ambient temperatures need to be above 45 F degrees with slab temperatures at or above 60 degrees F; humidity must be below 75%. These conditions can be tough to achieve in certain new construction scenario but if they are not achieved the installation may suffer aesthetically and the

resins may not performed as designed. Consequently LSP can not be responsible for the performance of the flooring system installed under adverse conditions.

The initial layer is a urethane cement and as such is not sensitive to moisture migration through the substrate at reasonable levels. Concrete substrates should be checked for moisture migration using ASTM F 1869-98 calcium chloride test prior to installation to assure they are not extreme.

Features and benefits include:

- Clear and Decorative
- Low HAP
- Low VOC
- LEED Compliant
- 100% solids – solvent free
- Excellent Bond Strength
- Excellent Chemical Resistance
- Excellent Thermal properties
- Excellent impact resistance
- High Taber Resistance

The LSP Performance systems in general are composed of resins and aggregates which utilize the best available technology for safety, performance and lowest environmental impact. All products and systems are extensively field tested prior to use on live projects.

Limitations

LSP Performance flooring must not be used to bridge moving cracks or joints. Non-moving cracks or joints that must be over coated require rigid repairs or references and filled with a urethane caulk. Surface or air temperature must be between 65°F minimum and 80°F maximum and relative humidity below 75%. Lower temperatures will extend cure time and higher temperatures will reduce pot life and work life. Chemical resistance as depicted in the specification is a relative classification and we recommend testing the chemicals you use in your facility on test flooring samples before making your final selection.

2. General Information and Handling

Storage and Handling

Store at temperatures above 60 degrees F.

Product Health and Safety Information

Refer to container labels and Material Safety Data Sheets available from LSP for health, safety and environmental information. If necessary, call LSP at (800) 638-9874.

Applicable Standards

LSP resins have been tested in accordance with American Society for Testing and Materials (ASTM) methods. The USDA and FDA no longer regulate coatings used on floors, walls, and ceilings in food process areas, since the surfaces are not intended for food contact.

Mixing

The use of proper PPE is required when mixing catalysts.

Measure the resin into plastic, marked containers. Add liquids together and agitate using a jiffy paddle and low speed drill (400-600 rpm). Agitate for 2 minutes, and then scrape sides of container and mix for an additional minute. Avoid generating air bubbles and foam. Consider mixing small batches to reduce potential waste. To avoid exothermic reaction in mixing container, do not let mixed components sit in container. Immediately, pour the mixed binder resin onto the floor to be coated. Spread or finish material according to application instructions contained in LSP Technical Manual.

information and is neither a contract nor a product warranty. Your installation contract is provided by your LSP Associate Contractor. LSP's warranty to you is made solely in the LSP Single Source Limited Warranty for Labor and Material. Contact your Associate Contractor for the specific warranty document.

4. Maintenance

LSP Performance Systems are hard seamless surfaces that will provide years of life with little maintenance. For more detailed maintenance instructions, please request LSP Floor Maintenance Instructions. Periodic inspections by your LSP Associate Contractor are recommended to discuss ways to extend the life of the floor care.

3. Warranty

LSP Performance Systems are installed by LSP Associate Contractors and are available with the LSP Single Source Limited Warranty for Labor and Material. This Product Data Sheet is for your

SECTION 1 Product and Company Information

PRODUCT NAME: SeamTek® Chemical Resistant Hardener, CRH405 Chemtrec
GENERIC NAME: Epoxy Hardener 24 Hour Emergency Number 1-800-424-9300
Information Number: 1-800-666-6216
DISTRIBUTOR: LSP Performance Resins
 124 Speer Road
 Chestertown, MD 21620
 Comments: To the best of our knowledge, this Material Safety Data Sheet conforms to the requirements of US OSHA 29 CFR1910.1200, 91/155/ECC and Canadian Hazardous Products Act

SECTION 2 Hazards Identification

Emergency Overview OSHA Hazardous Target Organ Effect: Skin Sensitizer, Irritant Target Organs: Respiratory, eyes, Skin Physical Appearance: Viscous liquid Immediate Concerns: Skin Irritation		Potential Health Effects Skin: Will cause irritation and dermatitis, repeated overexposure will cause dermatitis and sensitization. Sensitized persons may experience rapid irritation of skin upon exposure. Inhalation and Ingestion: Irritation to system
Carcinogenicity: Not listed by NTP Not Listed by IARC Not Listed by OSHA	Reproductive Toxicity Reproductive Effects : Not Available Teratogenic Effects: Not Available	Signs and Symptoms of Overexposure: Irritation of Skin Medical Conditions Aggravated: Allergy, Skin Disorders

GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS

Health		Environmental	Physical
Acute Toxicity, Oral	Category 5	Not Classified	Not Classified
Skin Irritant	Category 2		
Serious Eye Damage	Category 1		
Skin Sensitization	Category 1		

Pictogram:



Signal Word Danger

Hazard Statements	Precautionary Statements
H303 May be harmful if swallowed	P280 Wear protective gloves/protective clothing/eye protection/face protection P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
H315 Causes skin irritation	
H317 May cause an allergic skin reaction	
H318 Causes serious eye damage	

SECTION 3 Composition / Information on Ingredients

Chemical Name	CAS	Wt%
Modified cycloaliphatic polyamines	Trade secret	
Benzyl alcohol	100-51-6	

SECTION 4 First Aid Measures

EYE CONTACT: Get medical attention immediately. Immediately flush eyes gently with large amounts of water, holding lids open for at least 20-30 minutes, retracting eyelids often. Check for, and remove contact lenses.

SKIN CONTACT: Get medical attention immediately. Flush contaminated skin with plenty of WATER. Do NOT wash with solvents. Wash contaminated clothing thoroughly with water before removing it or wear gloves. Continue to rinse for at least 10 minutes. May cause irritation and allergic reaction. Seek medical advice if irritation develops or persists.

INHALATION: Move exposed person to fresh air. Get medical attention immediately. If it is suspected that fumes are still present, the rescuer should wear an appropriate make of self contained breathing apparatus. Keep person warm and at rest. If not breathing or breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing air to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway

INGESTION: Get medical attention immediately. Wash out mouth with water. Move exposed person to fresh air. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.

Advice to physicians: Symptomatic and supportive therapy as needed. May aggravate skin conditions.

SECTION 5 Fire Fighting Measures

Conditions of Flammability

Not flammable or combustible

Suitable Extinguishing Media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Hazardous Decomposition Products

Hazardous decomposition products formed under fire conditions – Carbon Oxides

Fire Fighting Instructions

Do not enter fire area without proper protection. Wear self contained breathing apparatus (pressure-demand MSHA/NIOSH) approved or equivalent. See Section 10 - decomposition products possible. Fight fire from safe distance/protected location. Heat/impurities may increase temperature/build pressure/rupture closed containers, spreading fire, increasing risk of burns/injuries. Use water spray/fog for cooling.

SECTION 6 Accidental Release Measures

Personal Precautions

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).

Environmental Precautions

Avoid dispersal of spill material and runoff and contact with soil, waterways, drains and sewers. Notify authorities of any releases to sewers, soils, waterways or air.

Methods and Materials for Containment and Cleaning Up

Stop the leak if it can be done without risk. Move containers from the spill area. Prevent entry into sewers, water ways or soils. Contain and collect spillage with non-combustible, absorbent material such as sand, earth, vermiculite or diatomaceous earth. Place in container for disposal according to local regulations via a licensed waste disposal contractor. Contaminated absorbent materials may pose the same hazards as the spilled product. See section 1 for emergency contact information and section 13 for waste disposal.

SECTION 7 Handling and Storage

Precautions for Safe Handling Can cause skin and eye irritation and allergic skin reaction.

Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Conditions for Safe Storage

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

SECTION 8 Exposure Controls / Personal Protection

EXPOSURE GUIDELINES

Hazardous Component	PEL	STEL	TLV	Other
Modified cycloaliphatic polyamines	NE	NE	NE	NE
Benzyl alcohol	NE	NE	NE	NE

ENGINEERING CONTROLS Use local exhaust ventilation to maintain airborne concentrations below exposure limits. Respiratory protection may be required in addition to general room ventilation.

PERSONAL PROTECTIVE EQUIPMENT Use a properly fitted, air-purifying or air supplied respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

EYE PROTECTION Eye protection such as chemical splash goggles and/or face shield must be worn when possibility exists for eye contact due to splashing or spraying liquid, airborne particles or vapor. Contact lenses should not be worn.

SKIN AND BODY PROTECTION When skin contact is possible, protective clothing including gloves, apron, sleeves, boots, head and face protection should be worn. Gloves should be impervious neoprene or rubber. Use of barrier cream is recommended. Clean equipment thoroughly after each use. Discard contaminated leather shoes and canvas sneakers.

OTHER HYGENIC PRACTICES Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

OTHER WORK PRACTICES Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet facilities. Promptly remove soiled clothing and wash thoroughly before reuse. Shower after work using plenty of soap and water.

SECTION 9 Physical and Chemical Properties

Appearance	
Form	Liquid
Color	Light amber
pH	Not available
Melting/Freezing Temperature	40 C/ 104 F
Boiling Point	336 C/ 637 F
Flash Point	> 95 C/ 200 F
Ignition Temperature	Not available
Autoignition Temperature	Not available
Lower explosive limit; na	Upper explosive limit: na
Vapor Pressure	<0.1 mm Hg
Vapor Density (air=1)	Not available
Specific Gravity (water=1 @39.2F)	>1.01
Evaporation Rate (Bac=1)	None
Odor	amine
Odor threshold	Not available

SECTION 10 Stability and Reactivity

Chemical Stability

Stable under recommended storage conditions

Possibility of Hazardous Reactions

No data available

Conditions to Avoid

Avoid strong acids, bases in bulk and elevated temperatures

Materials to Avoid

Reactive or incompatible with: acids, oxidizers, amines

Hazardous Decomposition Products

Decomposition products formed under fire conditions may include: Carbon oxides, Nitrogen oxides, Aldehydes.

SECTION 11 Toxicological Information

Acute Toxicity

Oral LD50	Rat > 4000 mg/kg.
Dermal LD50	Rabbit 20,000 mg/kg
Inhalation LC50	No data available

Carcinogenicity

IARC: No component of this product presents at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC

Skin Corrosion/Irritation

Skin	Irritant
------	----------

ACGIH: No component of this product presents at levels greater than or equal to 0.1% is identified as carcinogen or potential carcinogen by ACGIH

Serious Eye Damage/Eye Irritation

Eye	Irritant
Eyes	Rabbit
Severe eye irritation – 24 H	

NTP: No component of this product presents at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP

Respiratory or Skin Sensitization

May cause skin or respiratory sensitization

Mutagenicity

Mouse	Skin
Carcinogenic by RTECS Criteria	
liver, ovarian, thyroid	

SECTION 12 Ecological Information

Aquatic Ecotoxicity

No data available

Biodegradability

Persistent	Not readily biodegradable
------------	---------------------------

Mobility in soil

No data available

SECTION 13 Disposal Considerations

Waste Disposal

The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residuals. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14 Transport Information

DOT (US)

Not Regulated

IMDG

Not Regulated

TDG

Not Regulated

SECTION 15 Regulatory Information

TSCA INVENTORY STATUS

All components are listed or exempt

OSHA HAZARDS

Skin Sensitizer	Irritant
Corrosive Material	

HMIS Classification

Health Hazard;	3	NFPA Rating	3
Flammability	1		0
Physical Hazards	0		0

SARA TITLE III: Section 311/312 Hazard Class

Acute Health Hazard, Chronic Health Hazard

SARA TITLE III: Section 313 (40CFR370)

This product does not contain a chemical which is listed in Section 313 at or above the de minimus concentrations

CERCLA Information (40CFR302.4)

This material contains no hazardous or extremely hazardous substances at or above the de minimus concentrations as defined by CERCLA or SARA Title III, and release is therefore not reportable.

California Proposition 65 Information:

This product contains, no listed substances known to the state of California to cause cancer and/or reproductive toxicity.

SECTION 16 Other Information

Some of the information presented and conclusions drawn herein are from sources other than direct test data on the product itself. The information in this MSDS was obtained from sources, which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable. This MSDS has been prepared in accordance with the requirements of the OSHA Hazard Communication Standard (29 CFR 1910.1200).

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or results to be obtained from the user thereof. LSP Performance Resins assumes no responsibility for personal injury or property damage to vendees, such as vendees or users assume all risks associated with the use of the material.

LSP PERFORMANCE RESINS
800.638.9874

124 Speer Road
FAX 410.778.3625

Chestertown, MD 21620
web www.lspinc.com

MATERIAL SAFETY DATA SHEET

SECTION 1 IDENTIFICATION

CLIFFORD W. ESTES CO., INC
40 VREELAND AVE STE 104
TOTOWA, NJ 07512

DATE: JANUARY 2005
PHONE: 973.890.1515

PRODUCT BRAND NAME: PERMACOLOR SURFACE AGGREGATES, REGULAR AND HP

PRODUCT IDENTIFICATION : BROADCAST(MED.&FINE), TROWEL-RITE (REGULAR AND SUPER), VARIOUS COLORS

CHEMICAL NAME: SILICON DIOXIDE (SIO2)

DEPARTMENT OF TRANSPORTATION: SAND, GRAVEL, NOIBN

CHEMICAL FAMILY: SILICA SAND

COLOR: TYPICAL COLORS

SECTION II HAZARDOUS INGREDIENTS

CHEMICAL NAME	% WT	CAS#	OSHA (PEL)	ACGIH (TLV)
SILICA SAND	94	14808-60-7		.1MG/M3
RESIN	4.95	NON-HAZARDOUS PROPRIETARY	N/A	N/A
TIO2	0.99	13463-67-7		
COLORANTS ORGANIC AND INORGANIC	0.06	NON-HAZARDOUS		

* Special Statement regarding Hazardous ingredients:

Although these products are composed primarily of Silica Sand (SIO2), and such sand is potentially a source for respirable dust, the sand particles are thoroughly encapsulated in a coating which captures all dust and should, under normal circumstances, prevent any normal release of silica dust to the workplace. See page two, Section VIII for further information on handling.

SECTION III PHYSICAL DATA

BOILING POINT: NONE
VAPOR PRESSURE: NONE
VAPOR DENSITY: NONE
% VOLATILES :<1%
APPEARANCE: SAND OR AGGREGATE, TYPICAL COLORS

SPECIFIC GRAVITY: 2.65
PH: INERT
EVAPORATION RATE: N/A
SOLUBILITY IN WATER: INSOLUBLE

HIMS RATINGS

HEALTH	0*
FLAMABILITY	0
REACTIVITY	0

*REFER TO SPECIAL STATEMENT ABOVE

SECTION IV FIRE AND EXPLOSION HAZARD

FLASH POINT: NON-FLAMMABLE

FLAMMABLE LIMITS: LEL- N/A , UEL - N/A

UNUSUAL FIRE AND EXPLOSION HAZARDS: Products of combustion may include irritating gases.

SECTION V HEALTH AND SAFETY

THRESHOLD LIMIT VALUE: (SEE PAGE ONE)

EFFECTS OF OVER EXPOSURE: Prolonged inhalation of mineral dust may cause delayed lung injury.

EMERGENCY AND FIRST AID PROCEDURES: - EYES, Remove in the same manner as one would remove any foreign particle.

SECTION VI REACTIVITY DATA

STABILITY: Stable

INCOMPATIBILITY: Dissolves in hydrofluoric acid

CONDITIONS TO AVOID: None Known

SECTION VII SPILL/LEAK PROCEDURES

1. Clean up using dustless procedures. Use water and/or vacuum.
2. WASTE DISPOSAL: Dispose using locally approved waste disposal sites.

SECTION VIII SPECIAL PROTECTION

Use of this product under normal and recommended conditions and specifications will pose no known hazards. However, if surfaces using this product are subjected to sanding or grinding as might occur for maintenance purposes, and such treatment produces respirable dust, then proper ventilation and breathing apparatus should be used. Under such conditions, NIOSH-BOM approved respirators should be worn.

GLOVES: Optional

EYE PROTECTION: Full eye zone goggles should be worn.

SECTION IX SPECIAL PRECAUTIONS

1. USE DUSTLESS PROCEDURES DURING HANDLING, STORAGE, AND CLEAN-UP
2. PRACTICE GOOD HOUSEKEEPING. MAINTAIN VENTILATION. POST WARNING TO EMPLOYEES WHERE PRODUCT IS USED, STORED, AND HANDLED.



SECTION 1 Product and Company Information

PRODUCT NAME: SeamTek® Standard Hardener, SH101 Chemtrec
GENERIC NAME: Epoxy Hardener 24 Hour Emergency Number 1-800-424-9300
Information Number: 1-800-666-6216

DISTRIBUTOR: LSP Performance Resins
 124 Speer Road
 Chestertown, MD 21620

Comments: To the best of our knowledge, this Material Safety Data Sheet conforms to the requirements of US OSHA 29 CFR1910.1200, 91/155/ECC and Canadian Hazardous Products Act

SECTION 2 Hazards Identification

<p>Emergency Overview OSHA Hazardous Target Organ Effect: Skin Sensitizer, Irritant Target Organs: Respiratory, eyes, Skin Physical Appearance: Viscous liquid Immediate Concerns: Skin Irritation</p>	<p>Potential Health Effects Skin: Will cause irritation and dermatitis, repeated overexposure will cause dermatitis and sensitization. Sensitized persons may experience rapid irritation of skin upon exposure. Inhalation and Ingestion: Irritation to system</p>	
<p>Carcinogenicity: Not listed by NTP Not Listed by IARC Not Listed by OSHA</p>	<p>Reproductive Toxicity Reproductive Effects : Not Available Teratogenic Effects: Not Available</p>	
GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS		
Health	Environmental	Physical
Acute Toxicity, Oral Skin Irritant Serious Eye Damage Skin Sensitization	Category 5 Category 2 Category 1 Category 1 Not Classified	Not Classified
<p>Pictogram:  </p> <p>Signal Word Danger</p>		
Hazard Statements		Precautionary Statements
H303 Maybe harmful if swallowed H315 Causes skin irritation H317 May cause an allergic skin reaction H318 Causes serious eye damage	P280 Wear protective gloves/protective clothing/eye protection/face protection P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	

SECTION 3 Composition / Information on Ingredients

Chemical Name	CAS	Wt%
polyoxalkyleneamine	9046100	
Triethylene glycol diamine	929599	
Epoxy curing agent	mixture	
Alkyl phenol	84852153	
Alpha hydroxyl toluene	100-51-6	

SECTION 4 First Aid Measures

EYE CONTACT: Get medical attention immediately. Immediately flush eyes gently with large amounts of water, holding lids open for at least 20-30 minutes, retracting eyelids often. Check for, and remove contact lenses.

SKIN CONTACT: Get medical attention immediately. Flush contaminated skin with plenty of WATER. Do NOT wash with solvents. Wash contaminated clothing thoroughly with water before removing it or wear gloves. Continue to rinse for at least 10 minutes. May cause irritation and allergic reaction. Seek medical advice if irritation develops or persists.

INHALATION: Move exposed person to fresh air. Get medical attention immediately. If it is suspected that fumes are still present, the rescuer should wear an appropriate make of self contained breathing apparatus. Keep person warm and at rest. If not breathing or breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing air to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway

INGESTION: Get medical attention immediately. Wash out mouth with water. Move exposed person to fresh air. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.

Advice to physicians: Symptomatic and supportive therapy as needed. May aggravate skin conditions.

SECTION 5 Fire Fighting Measures

Conditions of Flammability

Not flammable or combustible

Suitable Extinguishing Media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Hazardous Decomposition Products

Hazardous decomposition products formed under fire conditions – Carbon Oxides

Fire Fighting Instructions

Do not enter fire area without proper protection. Wear self contained breathing apparatus (pressure-demand MSHA/NIOSH) approved or equivalent. See Section 10 - decomposition products possible. Fight fire from safe distance/protected location. Heat/impurities may increase temperature/build pressure/rupture closed containers, spreading fire, increasing risk of burns/injuries. Use water spray/fog for cooling.

SECTION 6 Accidental Release Measures

Personal Precautions

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).

Environmental Precautions

Avoid dispersal of spill material and runoff and contact with soil, waterways, drains and sewers. Notify authorities of any releases to sewers, soils, waterways or air.

Methods and Materials for Containment and Cleaning Up

Stop the leak if it can be done without risk. Move containers from the spill area. Prevent entry into sewers, water ways or soils. Contain and collect spillage with non-combustible, absorbent material such as sand, earth, vermiculite or diatomaceous earth. Place in container for disposal according to local regulations via a licensed waste disposal contractor. Contaminated absorbent materials may pose the same hazards as the spilled product. See section 1 for emergency contact information and section 13 for waste disposal.

SECTION 7 Handling and Storage

Precautions for Safe Handling Can cause skin and eye irritation and allergic skin reaction.

Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Conditions for Safe Storage

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

SECTION 8 Exposure Controls / Personal Protection

EXPOSURE GUIDELINES

Hazardous Component	PEL	STEL	TLV	Other
polyoxalkyleneamine	NE	NE	NE	NE
Triethylene glycol diamine	NE	NE	NE	NE
Epoxy curing agent	NE	NE	NE	NE
Alkyl phenol	NE	NE	NE	NE
Alpha hydroxyl toluene	NE	NE	NE	NE

ENGINEERING CONTROLS Use local exhaust ventilation to maintain airborne concentrations below exposure limits. Respiratory protection may be required in addition to general room ventilation.

PERSONAL PROTECTIVE EQUIPMENT Use a properly fitted, air-purifying or air supplied respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

EYE PROTECTION Eye protection such as chemical splash goggles and/or face shield must be worn when possibility exists for eye contact due to splashing or spraying liquid, airborne particles or vapor. Contact lenses should not be worn.

SKIN AND BODY PROTECTION When skin contact is possible, protective clothing including gloves, apron, sleeves, boots, head and face protection should be worn. Gloves should be impervious neoprene or rubber. Use of barrier cream is recommended. Clean equipment thoroughly after each use. Discard contaminated leather shoes and canvas sneakers.

OTHER HYGENIC PRACTICES Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

OTHER WORK PRACTICES Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet facilities. Promptly remove soiled clothing and wash thoroughly before reuse. Shower after work using plenty of soap and water.

SECTION 9 Physical and Chemical Properties

Appearance	
Form	Liquid
Color	Colorless to Amber
pH	Not available
Melting/Freezing Temperature	40 C/ 104 F
Boiling Point	336 C/ 637 F
Flash Point	> 95 C/ 200 F
Ignition Temperature	Not available
Autoignition Temperature	Not available
Lower explosive limit; na	Upper explosive limit: na
Vapor Pressure	<0.1 mm Hg
Vapor Density (air=1)	Not available
Specific Gravity (water=1 @39.2F)	1.14 at 25 C/77F
Evaporation Rate (Bac=1)	None
Odor	Light possible phenol
Odor threshold	Not available

SECTION 10 Stability and Reactivity

Chemical Stability

Stable under recommended storage conditions

Possibility of Hazardous Reactions

No data available

Conditions to Avoid

Avoid strong acids, bases in bulk and elevated temperatures

Materials to Avoid

Reactive or incompatible with: acids, oxidizers, amines

Hazardous Decomposition Products

Decomposition products formed under fire conditions may include: Carbon oxides, Nitrogen oxides, Aldehydes.

SECTION 11 Toxicological Information

Acute Toxicity

Oral LD50	Rat > 4000 mg/kg.
Dermal LD50	Rabbit 20,000 mg/kg
Inhalation LC50	No data available

Carcinogenicity

IARC: No component of this product presents at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC

Skin Corrosion/Irritation

Skin	Irritant
------	----------

ACGIH: No component of this product presents at levels greater than or equal to 0.1% is identified as carcinogen or potential carcinogen by ACGIH

Serious Eye Damage/Eye Irritation

Eye	Irritant
Eyes	Rabbit
Severe eye irritation – 24 H	

NTP: No component of this product presents at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP

Respiratory or Skin Sensitization

May cause skin or respiratory sensitization

Mutagenicity

Mouse	Skin
Carcinogenic by RTECS Criteria	
liver, ovarian, thyroid	

SECTION 12 Ecological Information

Aquatic Ecotoxicity

No data available

Biodegradability

Persistent	Not readily biodegradable
------------	---------------------------

Mobility in soil

No data available

SECTION 13 Disposal Considerations

Waste Disposal

The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residuals. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14 Transport Information

DOT (US)

Not Regulated

IMDG

Not Regulated

TDG

Not Regulated

SECTION 15 Regulatory Information

TSCA INVENTORY STATUS

All components are listed or exempt

OSHA HAZARDS

Skin Sensitizer	Irritant
Corrosive Material	

HMIS Classification

Health Hazard;	3
Flammability	1
Physical Hazards	0

NFPA Rating

3
0
0

SARA TITLE III: Section 311/312 Hazard Class

Acute Health Hazard, Chronic Health Hazard

SARA TITLE III: Section 313 (40CFR370)

This product does not contain a chemical which is listed in Section 313 at or above the de minimus concentrations

CERCLA Information (40CFR302.4)

This material contains no hazardous or extremely hazardous substances at or above the de minimus concentrations as defined by CERCLA or SARA Title III, and release is therefore not reportable.

California Proposition 65 Information:

This product contains, no listed substances known to the state of California to cause cancer and/or reproductive toxicity.

SECTION 16 Other Information

Some of the information presented and conclusions drawn herein are from sources other than direct test data on the product itself. The information in this MSDS was obtained from sources, which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable. This MSDS has been prepared in accordance with the requirements of the OSHA Hazard Communication Standard (29 CFR 1910.1200).

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or results to be obtained from the user thereof. LSP Performance Resins assumes no responsibility for personal injury or property damage to vendees, such as vendees or users assume all risks associated with the use of the material.

SECTION 1 Product and Company Information

PRODUCT NAME: SeamTek® Standard Resin, SR101 Chemtrec
GENERIC NAME: Epoxy Resin 24 Hour Emergency Number 1-800-424-9300
Information Number: 1-800-666-6216

DISTRIBUTOR: LSP Performance Resins
 124 Speer Road
 Chestertown, MD 21620


Comments: To the best of our knowledge, this Material Safety Data Sheet conforms to the requirements of US OSHA 29 CFR1910.1200, 91/155/ECC and Canadian Hazardous Products Act

SECTION 2 Hazards Identification

<p>Emergency Overview OSHA Hazardous Target Organ Effect: Skin Sensitizer, Irritant Target Organs: Respiratory, eyes, Skin Physical Appearance: Viscous liquid Immediate Concerns: Skin Irritation</p>		<p>Potential Health Effects Skin: Will cause irritation and dermatitis, repeated overexposure will cause dermatitis and sensitization. Sensitized persons may experience rapid irritation of skin upon exposure. Inhalation and Ingestion: Irritation to system</p>	
<p>Carcinogenicity: Not listed by NTP Not Listed by IARC Not Listed by OSHA</p>	<p>Reproductive Toxicity Reproductive Effects : Not Available Teratogenic Effects: Not Available</p>	<p>Signs and Symptoms of Overexposure: Irritation of Skin Medical Conditions Aggravated: Allergy, Skin Disorders</p>	

GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS

Health		Environmental	Physical
Acute Toxicity, Oral Skin Irritant Serious Eye Damage Skin Sensitization	Category 5 Category 2 Category 1 Category 1	Not Classified	Not Classified

Pictogram: 

Signal Word **Danger**

Hazard Statements	Precautionary Statements
H303 Maybe harmful if swallowed H315 Causes skin irritation H317 May cause an allergic skin reaction H318 Causes serious eye damage	P280 Wear protective gloves/protective clothing/eye protection/face protection P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

SECTION 3 Composition / Information on Ingredients

Chemical Name	CAS	Wt%
diglycidyl ether bisphenol A epoxy resin	25085-99-8	
Aliphatic epoxide	68609-97-2	
Alkylated phenol	AN123581	
2-methyl-2,4-pentanediol	107-41-5	
Alkyl phenol	84852153	

SECTION 4 First Aid Measures

EYE CONTACT: Get medical attention immediately. Immediately flush eyes gently with large amounts of water, holding lids open for at least 20-30 minutes, retracting eyelids often. Check for, and remove contact lenses.

SKIN CONTACT: Get medical attention immediately. Flush contaminated skin with plenty of WATER. Do NOT wash with solvents. Wash contaminated clothing thoroughly with water before removing it or wear gloves. Continue to rinse for at least 10 minutes. May cause irritation and allergic reaction. Seek medical advice if irritation develops or persists.

INHALATION: Move exposed person to fresh air. Get medical attention immediately. If it is suspected that fumes are still present, the rescuer should wear an appropriate make of self contained breathing apparatus. Keep person warm and at rest. If not breathing or breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing air to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway

INGESTION: Get medical attention immediately. Wash out mouth with water. Move exposed person to fresh air. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.

Advise to physicians: Symptomatic and supportive therapy as needed. May aggravate skin conditions.

SECTION 5 Fire Fighting Measures

Conditions of Flammability

Not flammable or combustible

Suitable Extinguishing Media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Hazardous Decomposition Products

Hazardous decomposition products formed under fire conditions – Carbon Oxides

Fire Fighting Instructions

Do not enter fire area without proper protection. Wear self contained breathing apparatus (pressure-demand MSHA/NIOSH) approved or equivalent. See Section 10 - decomposition products possible. Fight fire from safe distance/protected location. Heat/impurities may increase temperature/build pressure/rupture closed containers, spreading fire, increasing risk of burns/injuries. Use water spray/fog for cooling.

SECTION 6 Accidental Release Measures

Personal Precautions

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).

Environmental Precautions

Avoid dispersal of spill material and runoff and contact with soil, waterways, drains and sewers. Notify authorities of any releases to sewers, soils, waterways or air.

Methods and Materials for Containment and Cleaning Up

Stop the leak if it can be done without risk. Move containers from the spill area. Prevent entry into sewers, water ways or soils. Contain and collect spillage with non-combustible, absorbent material such as sand, earth, vermiculite or diatomaceous earth. Place in container for disposal according to local regulations via a licensed waste disposal contractor. Contaminated absorbent materials may pose the same hazards as the spilled product. See section 1 for emergency contact information and section 13 for waste disposal.

SECTION 7 Handling and Storage

Precautions for Safe Handling

Can cause skin and eye irritation and allergic skin reaction.

Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not

reuse container.

Conditions for Safe Storage

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

SECTION 8 Exposure Controls / Personal Protection

EXPOSURE GUIDELINES

Hazardous Component	PEL	STEL	TLV	Other
diglycidyl ether bisphenol A epoxy resin	NE	NE	NE	NE
Aliphatic epoxide	NE	NE	NE	NE
Alkylated phenol	NE	NE	NE	NE
2-methyl-2,4-pentenediol	25 ppm	NE	25 ppm	NE
Alkyl phenol	NE	NE	NE	NE

ENGINEERING CONTROLS Use local exhaust ventilation to maintain airborne concentrations below exposure limits. Respiratory protection may be required in addition to general room ventilation.

PERSONAL PROTECTIVE EQUIPMENT Use a properly fitted, air-purifying or air supplied respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

EYE PROTECTION Eye protection such as chemical splash goggles and/or face shield must be worn when possibility exists for eye contact due to splashing or spraying liquid, airborne particles or vapor. Contact lenses should not be worn.

SKIN AND BODY PROTECTION When skin contact is possible, protective clothing including gloves, apron, sleeves, boots, head and face protection should be worn. Gloves should be impervious neoprene or rubber. Use of barrier cream is recommended. Clean equipment thoroughly after each use. Discard contaminated leather shoes and canvas sneakers.

OTHER HYGENIC PRACTICES Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

OTHER WORK PRACTICES Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet facilities. Promptly remove soiled clothing and wash thoroughly before reuse. Shower after work using plenty of soap and water.

SECTION 9 Physical and Chemical Properties

Appearance	
Form	Liquid
Color	Colorless to Amber
pH	Not available
Melting/Freezing Temperature	40 C/ 104 F
Boiling Point	336 C/ 637 F
Flash Point	> 95 C/ 200 F
Ignition Temperature	Not available
Autoignition Temperature	Not available
Lower explosive limit; na	Upper explosive limit: na
Vapor Pressure	<0.1 mm Hg
Vapor Density (air=1)	Not available
Specific Gravity (water=1 @39.2F)	1.14 at 25 C/77F
Evaporation Rate (Bac=1)	None
Odor	Light possible phenol
Odor threshold	Not available

SECTION 10 Stability and Reactivity

Chemical Stability
 Stable under recommended storage conditions

Possibility of Hazardous Reactions
 No data available

Conditions to Avoid
 Avoid strong acids, bases in bulk and elevated temperatures

Materials to Avoid
 Reactive or incompatible with: acids, oxidizers, amines

Hazardous Decomposition Products
 Decomposition products formed under fire conditions may include: Carbon oxides, Nitrogen oxides, Aldehydes.

SECTION 11 Toxicological Information

<p>Acute Toxicity</p> <table border="0"> <tr> <td>Oral LD50</td> <td>Rat > 4000 mg/kg.</td> </tr> <tr> <td>Dermal LD50</td> <td>Rabbit 20,000 mg/kg</td> </tr> <tr> <td>Inhalation LC50</td> <td>No data available</td> </tr> </table> <p>Skin Corrosion/Irritation</p> <table border="0"> <tr> <td>Skin</td> <td>Irritant</td> </tr> </table> <p>Serious Eye Damage/Eye Irritation</p> <table border="0"> <tr> <td>Eye</td> <td>Irritant</td> </tr> <tr> <td>Eyes</td> <td>Rabbit</td> </tr> <tr> <td colspan="2">Severe eye irritation – 24 H</td> </tr> </table> <p>Respiratory or Skin Sensitization May cause skin or respiratory sensitization</p> <p>Mutagenicity</p> <table border="0"> <tr> <td>Mouse</td> <td>Skin</td> </tr> <tr> <td colspan="2">Carcinogenic by RTECS Criteria</td> </tr> <tr> <td colspan="2">liver, ovarian, thyroid</td> </tr> </table>	Oral LD50	Rat > 4000 mg/kg.	Dermal LD50	Rabbit 20,000 mg/kg	Inhalation LC50	No data available	Skin	Irritant	Eye	Irritant	Eyes	Rabbit	Severe eye irritation – 24 H		Mouse	Skin	Carcinogenic by RTECS Criteria		liver, ovarian, thyroid		<p>Carcinogenicity</p> <p>IARC: No component of this product presents at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC</p> <p>ACGIH: No component of this product presents at levels greater than or equal to 0.1% is identified as carcinogen or potential carcinogen by ACGIH</p> <p>NTP: No component of this product presents at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP</p>
Oral LD50	Rat > 4000 mg/kg.																				
Dermal LD50	Rabbit 20,000 mg/kg																				
Inhalation LC50	No data available																				
Skin	Irritant																				
Eye	Irritant																				
Eyes	Rabbit																				
Severe eye irritation – 24 H																					
Mouse	Skin																				
Carcinogenic by RTECS Criteria																					
liver, ovarian, thyroid																					

SECTION 12 Ecological Information

Aquatic Ecotoxicity
 No data available

Biodegradability
 Persistent Not readily biodegradable

Mobility in soil
 No data available

SECTION 13 Disposal Considerations

Waste Disposal

The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residuals. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14 Transport Information

DOT (US)

Not Regulated

IMDG

Not Regulated

TDG

Not Regulated

SECTION 15 Regulatory Information

TSCA INVENTORY STATUS

All components are listed or exempt

OSHA HAZARDS

Skin Sensitizer Irritant
Corrosive Material

HMIS Classification

Health Hazard;	2	NFPA Rating	2
Flammability	1		0
Physical Hazards	0		0

SARA TITLE III: Section 311/312 Hazard Class

Acute Health Hazard, Chronic Health Hazard

SARA TITLE III: Section 313 (40CFR370)

This product does not contain a chemical which is listed in Section 313 at or above the de minimus concentrations

CERCLA Information (40CFR302.4)

This material contains no hazardous or extremely hazardous substances at or above the de minimus concentrations as defined by CERCLA or SARA Title III, and release is therefore not reportable.

California Proposition 65 Information:


This product contains, no listed substances known to the state of California to cause cancer and/or reproductive toxicity.

SECTION 16 Other Information

Some of the information presented and conclusions drawn herein are from sources other than direct test data on the product itself. The information in this MSDS was obtained from sources, which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable. This MSDS has been prepared in accordance with the requirements of the OSHA Hazard Communication Standard (29 CFR 1910.1200).

UTEK A UTEK PART A	
SAFETY DATA SHEET Effective Date 01/01/2015	HMIS Ratings Health – 1 Flammability – 1 Reactivity – 0

SECTION 1 Product and Company Information	
PRODUCT NAME: UTEK PART A	Chemtrec
GENERIC NAME: Heavy Duty, Cementitious Urethane Part A	24 Hour Emergency Number 1-800-424-9300 Information Number: 1-800-666-6216
DISTRIBUTOR: LSP Performance Resins 124 Speer Road Chestertown, MD 21620	
Comments: To the best of our knowledge, this Material Safety Data Sheet conforms to the requirements of US OSHA 29 CFR1910.1200, 91/155/ECC and Canadian Hazardous Products Act	

SECTION 2 Hazards Identification		
Emergency Overview OSHA Hazardous Not considered hazardous		Potential Health Effects Inhalation: May cause irritation to the respiratory tract. Eyes: May cause eye irritation. Ingestion: May be harmful if swallowed. Skin: May cause irritation and sensitization of the skin
Carcinogenicity: Not listed by NTP Not Listed by IARC Not Listed by OSHA	Reproductive Toxicity Reproductive Effects : Not Available Teratogenic Effects: No evidence of mutagenetic effects	Signs and Symptoms of Overexposure: There are no known health effects associated with chronic exposure to this product.
GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS		
Health	Environmental	Physical
Eye Irritant Skin Irritant Respiratory Irritant	Not Classified	Not Classified
Pictogram: 		
Hazard Statements		Precautionary Statements

SECTION 3 Composition / Information on Ingredients		
Chemical Name	CAS	Wt%

SECTION 4 First Aid Measures
ADVISE TO PHYSICIANS
First Aid - Eye Contact: If material gets into eyes, flush with water immediately for 15 minutes. Consult a physician.
First Aid - Skin Contact: In case of contact, wash skin immediately with soap and water.
First Aid - Inhalation: If inhaled, remove to fresh air. Administer oxygen if necessary. Consult a physician if symptoms persist or exposure was severe.
First Aid - Ingestion: If swallowed do not induce vomiting. Seek immediate medical attention.

UTEK A UTEK PART A
<div style="display: flex; justify-content: space-between;"> <div style="width: 70%;"> <p>SAFETY DATA SHEET Effective Date 01/01/2015</p> </div> <div style="width: 25%; text-align: right;"> <p>HMIS Ratings Health – 1 Flammability – 1 Reactivity – 0</p> </div> </div>

SECTION 5 Fire Fighting Measures

Flash Point, F: 288F (142C) (Setaflash) **Lower Explosive Limit, %:** N/A
Upper Explosive Limit, %: N/A

Extinguishing Media: Carbon Dioxide, Dry Chemical, Foam, Water Fog

Unusual Fire And Explosion Hazards: None known.

Special Firefighting Procedures: Evacuate hazard area of unprotected personnel. Use a NIOSH approved self-contained breathing unit and complete body protection. Cool surrounding containers with water in case of fire exposure.

SECTION 6 Accidental Release Measures

Steps To Be Taken If Material Is Released Or Spilled: Use personal protective equipment as necessary. Absorb with suitable chemical absorbent. Dispose of material in accordance with all federal, state and local regulations.

SECTION 7 Handling and Storage

Handling: Do not get in eyes, on skin, or on clothing. Keep container tightly closed when not in use. Wear personal protection equipment. Do not breathe vapors. Wash thoroughly after handling. Use only in accordance with Verdia application instructions, container label and Product Data Sheet.

Storage: Keep containers closed. Store in a cool, dry place with adequate ventilation.

SECTION 8 Exposure Controls / Personal Protection

EXPOSURE GUIDELINES

Hazardous Component	PEL	STEL	TLV	Other

Engineering Controls: Use explosion-proof ventilation when required to keep below health exposure guidelines and Lower Explosion Limit (LEL).

Respiratory Protection: Use only with ventilation to keep levels below exposure guidelines listed in Section 2. User should test and monitor exposure levels to ensure all personnel are below guidelines. Follow all current OSHA requirements for respirator use.

Skin Protection: Recommend impervious gloves and clothing to avoid skin contact. If material penetrates to skin, change gloves and clothing. The use of protective creams may be beneficial to certain individuals. Protective creams should be applied before exposure.

Eye Protection: Recommend safety glasses with side shields or chemical goggles to avoid eye contact.

Other protective equipment: Eye wash and safety showers should be readily available.

Hygienic Practices: Wash with soap and water before eating, drinking, smoking, applying cosmetics, or using toilet facilities. Use of a hand cleaner is recommended. Launder contaminated clothing before reuse. Leather shoes can absorb and allow hazardous materials to pass through. Check shoes carefully after soaking before reuse.

SECTION 9 Physical and Chemical Properties

Form Color pH Melting/Freezing Temperature Boiling Point	liquid white N/DA N/A
--	--------------------------------

UTEK A UTEK PART A

SAFETY DATA SHEET
Effective Date 01/01/2015

HMIS Ratings
Health – 1
Flammability – 1
Reactivity – 0

Ignition Temperature	Not available
Flash Point	.60 °F (192.00 °C) estimated
Lower explosive limit; na	Upper explosive limit: na
Vapor Pressure	N/P
Vapor Density (air=1)	N/P
Specific Gravity (water=1 @39.2F)	
Evaporation Rate (Bac=1)	N/P
Odor	Not available
Odor threshold	Not available
Percent Volatiles	N/P
Relative Density	1.0
Solubility	Water soluble

SECTION 10 Stability and Reactivity

THIS PRODUCT IS STABLE
CONDITIONS AND MATERIALS TO AVOID - Frost
Incomparable material – none known
HAZARDOUS DECOMPOSITION PRODUCTS
Will not occur

SECTION 11 Toxicological Information

Local effects	None known
Chronic effects	None Known
Carcinogenicity	This product is NOT considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA

SECTION 12 Ecological Information

Persistence and degradability Prevent product from entering drains

SECTION 13 Disposal Considerations

Dispose of in accordance with State, Local, and Federal Environmental regulations. Responsibility for proper waste disposal is with the owner of the waste.

SECTION 14 Transport Information

DOT Proper Shipping Name:	Not Regulated	Packaging Group:	N/A
DOT Hazard Class:	None	Hazard Subclass:	N/A
DOT UN/NA Number:	None	Resp. Guide Page:	N/A
General DOT IATA:	Not Regulated as Dangerous Goods		

SECTION 15 Regulatory Information

CERCLA - SARA HAZARD CATEGORY

This product has been reviewed according to the EPA Hazard Categories promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD

UTEK A UTEK PART A

SAFETY DATA SHEET
Effective Date 01/01/2015

HMIS Ratings
Health – 1
Flammability – 1
Reactivity – 0

SARA SECTION 313

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Section 313 Substances exist in this product

TOXIC SUBSTANCES CONTROL ACT

All components of this product are listed on the TSCA inventory.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(B) Substances exist in this product

U.S. STATE REGULATIONS AS FOLLOWS: NEW JERSEY RIGHT-TO-KNOW

The following materials are non-hazardous, but are among the top five components in this product.

<u>Chemical Name</u>	<u>CAS Number</u>
CASTOR OIL	8001-79-4
PINE OIL	8002-09-3
PROPRIETARY SURFACTANT	TRADE SECRET
TRADE SECRET	TRADE SECRET
POLYOL	TRADE SECRET

PENNSYLVANIARIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at greater than 3%.

<u>Chemical Name</u>	<u>CAS Number</u>
CASTOR OIL	8001-79-4
PINE OIL	8002-09-3
PROPRIETARY SURFACTANT	TRADE SECRET

CALIFORNIA PROPOSITION 65

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

No California Proposition 65 Carcinogens exist

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards:

No California Proposition 65 Reproductive Toxins exist **INTERNATIONAL REGULATIONS AS**

FOLLOWS: CANADIAN WHMIS

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

CANADIAN WHMIS CLASS: D2B

UTEK A UTEK PART A	
SAFETY DATA SHEET Effective Date 01/01/2015	HMIS Ratings Health – 1 Flammability – 1 Reactivity – 0

SECTION 16 Other Information

HMIS Ratings
Health: 1 Flammability: 1 Reactivity: 0 Personal Protection: X

VOLATILE ORGANIC COMPOUNDS, GR/LTR MIXED (UNTHINNED): 0

REASON FOR REVISION: Changes made in Section(s): 2, 9, 11, and 15

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The information contained herein is, to the best of our knowledge and belief accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations

SECTION 1 Product and Company Information

PRODUCT NAME: UTEK PART B Chemtrec
GENERIC NAME: diphenylmethane-diisocyanate isomers 24 Hour Emergency Number 1-800-424-9300
 Information Number: 1-800-666-6216

DISTRIBUTOR: LSP Performance Resins
 124 Speer Road
 Chestertown, MD 21620

Comments: To the best of our knowledge, this Material Safety Data Sheet conforms to the requirements of US OSHA 29 CFR1910.1200, 91/155/ECC and Canadian Hazardous Products Act

SECTION 2 Hazards Identification

<p>Emergency Overview</p> <p>OSHA Hazardous Considered Hazardous</p> <p>When the base is mixed with the hardener an exothermic reaction starts (i.e. heat is generated). If the mix is not applied within 20 - 30 minutes some smoking may occur.</p>	<p>Potential Health Effects</p> <p>Inhalation: Harmful Eyes: May cause eye irritation. Ingestion: May be harmful if swallowed. Skin: May cause irritation and sensitization of the skin</p> <p>Harmful by inhalation. This hazard is most likely to arise when materials are heated, sprayed, used in a confined unventilated space or if correct handling procedures are not followed.</p> <p>Irritating to eyes, respiratory system and skin. In mild cases the affected person may experience slight irritation of the eyes, nose and throat, possibly combined with dryness of the throat. In more severe cases the person may suffer acute bronchial irritation and difficulty in breathing.</p> <p>May cause sensitization by inhalation and skin contact. Repeated and /or prolonged exposure may cause an allergic reaction/sensitization.</p>
---	---

<p>Carcinogenicity: Not listed by NTP Not Listed by IARC Not Listed by OSHA</p>	<p>Not listed Reproductive Effects : Not Available Teratogenic Effects: No evidence of mutagenetic effects</p>	<p>Signs and Symptoms of Overexposure: Bronchial irritation, difficulty breathing. Wheezing, tightness of chest, shortness of breath</p>
--	--	--

GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS

	Health	Environmental	Physical
Eye Irritant Skin Irritant, sensitizer Respiratory Irritant	Vapor, aerosol, liquid Moderate, may sensitize May sensitize	Not Classified	Not Classified

Pictogram:



Eyes Hazardous in case of eye contact (irritant)

Skin Hazardous in case of skin contact (irritant, sensitizer). Skin inflammation is characterized by itching, scaling or reddening.

Inhalation Hazardous in case of inhalation (lung irritant, lung sensitizer)

Ingestion Slightly hazardous in case of ingestion.

Medical Conditions aggravated by Overexposure: May cause or aggravate dermatitis and asthma.

SECTION 3 Composition / Information on Ingredients

Chemical Name	CAS	Wt%
diphenylmethane-diisocyanate isomers and homologues	9016-87-9	> 95

SECTION 4 First Aid Measures

First Aid - Eye Contact: If material gets into eyes, flush with water immediately for 15 minutes. Consult a physician.

First Aid - Skin Contact: In case of contact, wash skin immediately with soap and water.

First Aid - Inhalation: If inhaled, remove to fresh air. Administer oxygen if necessary. Consult a physician if symptoms persist or exposure was severe.

First Aid - Ingestion: If swallowed do not induce vomiting. Seek immediate medical attention.

SECTION 5 Fire Fighting Measures

Flash Point, F: 425F (218C)
(Cleveland O.C.)

Lower Explosive Limit, %: N/A
Upper Explosive Limit, %: N/A

Extinguishing Media: Carbon Dioxide, Dry Chemical, Foam

Unusual Fire and Explosion Hazards: Water contamination will produce Carbon Dioxide. Do not reseal contaminated containers as pressure buildup may rupture them.

Special Firefighting Procedures: Full emergency equipment with self-contained breathing apparatus and full protective clothing should be worn by firefighters. During a fire, MDI vapors and other irritating, highly toxic gases may be generated by thermal decomposition or combustion. (See stability and reactivity). At temperatures greater than 400F (204C), polymeric MDI can polymerize and decompose which can cause pressure build-up in closed containers. Explosive rupture is possible. Therefore, use cold water to cool fire-exposed containers. Evacuate hazard area of unprotected personnel. Use a NIOSH approved self-contained breathing unit and complete body protection. Cool surrounding containers with water in case of fire exposure. Since this product is water reactive, use DRY chemical powder for small fire. Use water spray, fog or foam for large fire. Do NOT use water jet.

SECTION 6 Accidental Release Measures

Steps to Be Taken If Material Is Released or Spilled: Use personal protective equipment as necessary. Absorb with suitable chemical absorbent. Dispose of material in accordance with all federal, state and local regulations. Evacuate and ventilate spill area; dike spill to prevent entry into water system; wear full protective equipment, including respiratory equipment during cleanup.

Major Spill: If temporary control of isocyanate is required, a blanket of protein foam (available at most fire departments) may be placed over the spill. Large quantities may be pumped into closed, but not sealed, container for disposal. **Minor Spill:** Absorb isocyanates with sawdust or other absorbent, shovel into suitable unsealed containers, transport to well-ventilated area (outside) and treat with neutralizing solution: mixture of water (80%) with non-ionic surfactant Tergitol TMN-10 (20%), or water (90%), concentrated ammonia (3 - 8%) and detergent (2%). Add about 10 parts neutralizer per part of isocyanate, with mixing. Allow to stand uncovered for 48 hours to let CO2 escape. Clean up: decontaminate floor with decontamination solution letting stand for at least 15 minutes.

Dispose of in accordance with local, state and federal regulations. Refer to Section 15 for SARA Title III and CERCLA information.

SECTION 7 Handling and Storage

Do not get in eyes, on skin, or on clothing. Keep container tightly closed when not in use. Wear personal protection equipment. Do not breathe vapors. Wash thoroughly after handling. Use only in accordance with manufacturer application instructions, container label and Product Data Sheet.

STORAGE: Keep away from heat, sparks, open flames and oxidizing agents. Keep containers closed. Store in a cool, dry place with adequate ventilation.

SECTION 8 Exposure Controls / Personal Protection

EXPOSURE GUIDELINES

Hazardous Component	PEL	STEL	TLV	Other
diphenylmethane-diisocyanate isomers	.20 mg/m ³ ceiling limit		.05 mg/m ³ 8hr/40 hrs/wk	.05 mg/m³ 10 hr/40 hrs/wk
				NIOSH REL/TWA

ENGINEERING CONTROLS: USE EXPLOSION-PROOF VENTILATION WHEN REQUIRED TO KEEP BELOW HEALTH EXPOSURE GUIDELINES AND LOWER EXPLOSION LIMIT (LEL).

RESPIRATORY PROTECTION: USE ONLY WITH VENTILATION TO KEEP LEVELS BELOW EXPOSURE GUIDELINES LISTED IN SECTION 2. USER SHOULD TEST AND MONITOR EXPOSURE LEVELS TO ENSURE ALL PERSONNEL ARE BELOW GUIDELINES. IF NOT SURE, OR NOT ABLE TO MONITOR, USE MSHA/NIOSH APPROVED SUPPLIED AIR RESPIRATOR. FOLLOW ALL CURRENT OSHA REQUIREMENTS FOR RESPIRATOR USE. FOR SILICA CONTAINING COATINGS IN A LIQUID STATE, AND/OR IF NO EXPOSURE LIMITS ARE ESTABLISHED IN SECTION 2 ABOVE, SUPPLIED AIR RESPIRATORS ARE GENERALLY NOT REQUIRED.

SKIN PROTECTION: RECOMMEND IMPERVIOUS GLOVES AND CLOTHING TO AVOID SKIN CONTACT. IF MATERIAL PENETRATES TO SKIN, CHANGE GLOVES AND CLOTHING. THE USE OF PROTECTIVE CREAMS MAY BE BENEFICIAL TO CERTAIN INDIVIDUALS.

PROTECTIVE CREAMS SHOULD BE APPLIED BEFORE EXPOSURE.

EYE PROTECTION: RECOMMEND SAFETY GLASSES WITH SIDE SHIELDS OR CHEMICAL GOGGLES TO AVOID EYE CONTACT.

OTHER PROTECTIVE EQUIPMENT: EYE WASH AND SAFETY SHOWERS SHOULD BE READILY AVAILABLE.

HYGIENIC PRACTICES: WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING, APPLYING COSMETICS, OR USING TOILET FACILITIES. USE OF A HAND CLEANER IS RECOMMENDED. LAUNDRER CONTAMINATED CLOTHING BEFORE REUSE. LEATHER SHOES CAN ABSORB AND ALLOW HAZARDOUS MATERIALS TO PASS THROUGH. CHECK SHOES CAREFULLY AFTER SOAKING BEFORE REUSE.

SECTION 9 Physical and Chemical Properties

Appearance	
Form	liquid
Color	brown
pH	N/DA
Melting/Freezing Temperature	N/A
Boiling Point	>550 deg – C decomposes
Ignition Temperature	Higher than 1110 deg C (350deg F) Flash Point
Autoignition Temperature	>600 deg C
Lower explosive limit; na	Upper explosive limit: na
Vapor Pressure	<0.0001 mbar at 70 °F (100Pa = 1 mbar)
Vapor Density (air=1)	.8 (Air =1)
Specific Gravity (water=1 @39.2F)	N/A
Evaporation Rate (Bac=1)	N/P
Odor	Slight musty
Odor threshold	Not available
Percent Volatiles	N/P
Viscosity	45 - 95 mPa's at 80 °F
Water Solubility	Insoluble, reacts to produce carbon dioxide and polyurea solid
Relative Density	1.24 at 70 °F

SECTION 10 Stability and Reactivity

CONDITIONS TO AVOID: CONTAMINATION WITH WATER. HEAT AND OPEN FLAMES.

INCOMPATIBILITY: WATER, AMINES, STRONG BASES, ALCOHOLS. WILL CAUSE CORROSION TO COPPER ALLOYS

HAZARDOUS DECOMPOSITION PRODUCTS: CARBON MONOXIDE, NITROGEN OXIDES, AND UNIDENTIFIED ORGANIC COMPOUNDS. CONSIDER ALL SMOKE AND FUMES FROM BURNING MATERIAL AS VERY HAZARDOUS. WELDING, CUTTING OR ABRASIVE GRINDING CAN CREATE SMOKE AND FUMES. DO NOT BREATHE ANY FUMES OR SMOKE FROM THESE OPERATIONS.

HAZARDOUS POLYMERIZATION: MAY OCCUR; CONTACT WITH MOISTURE, OTHER MATERIALS WHICH REACT WITH ISOCYANATES, OR TEMPERATURES ABOVE 400F (204 C), MAY CAUSE POLYMERIZATION.

STABILITY: THIS PRODUCT IS STABLE UNDER NORMAL STORAGE CONDITIONS.

SECTION 11 Toxicological Information

Acute oral toxicity

: LD₅₀ Oral (rat) : >5,000 mg/kg

Inhalation : LC₅₀ inhalation (rat) ca. 490 mg as aerosol/m³, 4 hrs exposure.
Concentration of saturated vapour: 0.09 mg/m³ at 80 °F

Irritation : Over exposure, especially when spraying without the necessary precautions, entails the risk of concentration dependant irritating effects on eyes, nose, throat and respiratory tract.
In mild cases the affected person may experience slight irritation of the eyes, nose and throat, possibly combined with dryness of the throat. In more severe cases the person may suffer acute bronchial irritation and difficulty in breathing.

Skin : Prolonged contact with the skin may cause tanning and irritant effects.
LD₅₀ Dermal (rabbit) > 5,000 mg/kg

Sensitisation : Repeated and /or prolonged exposure, especially at levels above the MEL, may cause an allergic reaction/respiratory sensitisation. Once sensitised, an individual may produce an allergic reaction every time they are in contact with isocyanates. Individuals who have developed sensitivity may experience wheezing, tightness of the chest and shortness of breath. A hyper-reactive response to even minimal concentrations of isocyanate may develop in sensitised persons.

The onset of respiratory symptoms (difficulty in breathing, coughing, asthma) may be delayed for several hours after exposure.

Repeated and/or prolonged skin contact may cause skin sensitisation. Animal studies have shown respiratory sensitisation can be induced by skin contact with known respiratory sensitisers, including isocyanates.

Animal studies have shown that respiratory sensitisation can be induced by skin contact with known respiratory sensitisers including diisocyanates.

Long term toxicity : Animal testing has shown no long term adverse effects at or below the MEL.
Chronic pulmonary irritation observed at high concentrations. There are reports that chronic exposure by inhalation may result in decreases in lung function.

Carcinogenicity : The classification for diphenylmethane diisocyanate has changed to carcinogenic, category 3, when it is in the form of respirable aerosol e.g. when sprayed.

Mutagenicity : There is no substantial evidence of mutagenic potential.

Reproductive toxicity : No birth defects seen in animal (rat) studies.
Fetotoxicity was observed at doses that were extremely toxic (including lethal) to the mother.
Fetotoxicity was not observed at doses that were not maternally toxic.

SECTION 12 Ecological Information

Ecological Information: Ecological data based on Polymeric MDI Biodegradation: 0%, Exposure time: 28 Days

Bioaccumulation:
 Rainbow Trout, Exposure time: 112d, <1 BCF Does not Bioaccumulate.

Acute and Prolonged Toxicity to Fish:
 LC0: >1,000 mg/l (Zebra fish (Brachydanio rerio), 96 hrs.) LC0: > 3,000 mg/l (Killifish (Oryzias latipes), 96h)

Acute toxicity to Aquatic Invertebrates:
 EC50: > 1,000 mg/l (Water flea (Daphnia magna), 24 hrs.)

Toxicity to aquatic plants:
 NOEC: 1640 mg/l, End Point: growth (Green algae (Scenedesmus subspicatus), 72 hrs.)

Toxicity to Microorganisms:
 EC50: > 100 mg/l, (Activated sludge microorganisms, 3 hrs.)

Ecological Data for 4,4'- Diphenylmethane Diisocyanate (MDI) Acute and Prolonged Toxicity to Fish:
 LC50: > 500 mg/l (Zebra fish (Brachydanio rerio), 24 hrs.)

Acute Toxicity to Aquatic Invertebrates:
 EC50: > 500 mg/l (Water flea (Daphnia magna), 24 hrs.)

SECTION 13 Disposal Considerations

Waste Disposal
 Dispose of in accordance with State, Local, and Federal Environmental regulations. Responsibility for proper waste disposal is with the owner of the waste.

SECTION 14 Transport Information

DOT Proper Shipping Name: Not Regulated	Packaging Group: N/A
DOT Hazard Class: None	Hazard Subclass: N/A
DOT UN/NA Number: None	Resp. Guide Page: N/A

SECTION 15 Regulatory Information

CERCLA - SARA HAZARD CATEGORY

THIS PRODUCT HAS BEEN REVIEWED ACCORDING TO THE EPA HAZARD CATEGORIES PROMULGATED UNDER SECTIONS 311 AND 312 OF THE SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986 (SARA TITLE III) AND IS CONSIDERED, UNDER APPLICABLE DEFINITIONS, TO MEET THE FOLLOWING CATEGORIES:

IMMEDIATE HEALTH HAZARD, CHRONIC HEALTH HAZARD, REACTION HAZARD

CANADIAN WHMIS CLASS: D1A, D2A, D2B

SARA SECTION 313

THIS PRODUCT CONTAINS THE FOLLOWING SUBSTANCES SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372:

<u>CHEMICAL NAME</u>	<u>CAS NUMBER</u>
POLYMERIC MDI	9016-87-9
4,4' MDI	101-68-8

TOXIC SUBSTANCES CONTROL ACT

ALL COMPONENTS OF THIS PRODUCT ARE LISTED ON THE TSCA INVENTORY.

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL SUBSTANCES SUBJECT TO THE REPORTING REQUIREMENTS OF TSCA 12(B) IF EXPORTED FROM THE UNITED STATES:

No TSCA 12(B) SUBSTANCES EXIST IN THIS PRODUCT

U.S. STATE REGULATIONS AS FOLLOWS: NEW JERSEY RIGHT-TO- KNOW

THE FOLLOWING MATERIALS ARE NON-HAZARDOUS, BUT ARE AMONG THE TOP FIVE COMPONENTS IN THIS PRODUCT.

PENNSYLVANIA RIGHT-TO-KNOW

THE FOLLOWING NON-HAZARDOUS INGREDIENTS ARE PRESENT IN THE PRODUCT AT GREATER THAN 3%.

CALIFORNIA PROPOSITION 65

WARNING: THE FOLLOWING INGREDIENTS PRESENT IN THE PRODUCT ARE KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER:

No CALIFORNIA PROPOSITION 65 CARCINOGENS EXIST

WARNING: THE FOLLOWING INGREDIENTS PRESENT IN THE PRODUCT ARE KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS, OR OTHER REPRODUCTIVE HAZARDS:

No CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS EXIST
INTERNATIONAL REGULATIONS AS FOLLOWS: CANADIAN WHMIS
 THIS MSDS HAS BEEN PREPARED IN COMPLIANCE WITH CONTROLLED PRODUCT REGULATIONS EXCEPT FOR THE USE OF THE 16 HEADINGS.

SECTION 16 Other Information

HMIS Ratings

Health: 3 Flammability: 1 Reactivity: 1 Personal Protection: X

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The information contained herein is, to the best of our knowledge and belief accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulation.

SECTION 1 Product and Company Information


PRODUCT NAME: UTEK C GENERIC NAME: Cement, Portland, Chemicals DISTRIBUTOR: LSP Performance Resins 124 Speer Road Chestertown, MD 21620	Chemtrec 24 Hour Emergency Number 1-800-424-9300 Information Number: 1-800-666-6216
Comments: To the best of our knowledge, this Material Safety Data Sheet conforms to the requirements of US OSHA 29 CFR1910.1200, 91/155/ECC and Canadian Hazardous Products Act	

SECTION 2 Hazards Identification

Emergency Overview OSHA Hazardous Considered Hazardous	Potential Health Effects Inhalation: May cause irritation to the respiratory tract. Eyes: Can cause eye irritation. Ingestion: May be harmful if swallowed. Skin: May cause irritation and sensitization of the skin
Carcinogenicity: Not listed by NTP Not Listed by IARC Not Listed by OSHA	Not listed Reproductive Effects : Not Available Teratogenic Effects: No evidence of mutagenetic effects
Signs and Symptoms of Overexposure:	

GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS

	Health	Environmental	Physical
Eye Irritant Skin Irritant, sensitizer Respiratory Irritant	Vapor, aerosol, liquid Moderate, may sensitize May sensitize	Not Classified	Not Classified

Pictogram: 

Risk of serious damage to eyes. The lime, calcium silicates and alkalis within the cement are partially soluble and when mixed with water will give rise to a potentially hazardous alkaline solution. The eyes are particularly vulnerable and damage will increase with contact time.

Contact with wet cement may cause irritation, dermatitis or burns.
 Contact between cement powder and body fluids (e.g. sweat and eye fluid) may also cause skin and respiratory irritation, dermatitis or burns.

Contains Chromium (VI), a skin sensitizer, and may produce an allergic eczema reaction.

Inhalation: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.

Eyes: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.

Ingestion: May be harmful if swallowed.

Skin: Alkaline. When product exposed to moisture, skin contact may produce burns or irritation.

POTENTIAL ACUTE HEALTH EFFECTS

Chronic effects: May cause sensitization by skin contact. Repeated inhalation of dust can produce varying degrees of respiratory irritation or lung damage.

Carcinogenicity: Contains material which can cause cancer. Risk of cancer depends on duration and level of exposure.

SECTION 3 Composition / Information on Ingredients

Chemical Name	EINECS No.	CAS No.	% by weight	Symbols and Risk Phrases
Cements	270-659-9	68475-76-3	5 - 15	Xi; R41.
Hydrated Lime	215-137-3	1305-62-0	< 10	Xi; R38. R41.
Silica Sand, Silicon dioxide	238-878-4	14808-60-7	> 30	None.
Respirable crystalline silica	-	14808-60-7	Trace	Xn; R48:R20.

SECTION 4 First Aid Measures

General Information: In case of accident or you feel unwell, seek medical advice and take the relevant safety data sheets.
 Never give anything by mouth to an unconscious person.

Inhalation : If irritation occurs, move to fresh air. If nose or airways become inflamed seek medical advice.
Skin contact : Wash with soap and plenty of water before continuing. If irritation, pain or other skin trouble occurs, seek medical advice. Contaminated clothing should be removed and washed thoroughly before re-use.

Eye Contact : Hold eyelids apart and immediately flush with plenty of water for at least 15 minutes. Seek medical advice immediately.

INGESTION : **WASH OUT MOUTH WITH WATER AND GIVE PATIENT PLENTY OF WATER TO DRINK**

PHYSICIAN: SYMPTOMATIC AND SUPPORTIVE THERAPY AS NEEDED. FOLLOWING SEVERE EXPOSURE MEDICAL FOLLOW-UP SHOULD BE MONITORED FOR AT LEAST 48

SECTION 5 Fire Fighting Measures

THIS MATERIAL IS NON-COMBUSTIBLE AND WILL NOT FACILITATE COMBUSTION WITH OTHER MATERIALS.

SECTION 6 Accidental Release Measures

- Personal precautions : Use personal protective equipment as detailed in Section 8.
- Ensure adequate ventilation.
- Environmental precautions : Avoid the formation of dust clouds.
- Methods for cleaning up : Sweep or preferably vacuum up and collect in suitable containers for disposal in accordance with Section 13. Avoid creating a dust cloud, dampen with water if possible. Addition of water may result in the product hardening in situ if not removed quickly.

SECTION 7 Handling and Storage

Handling : Provide sufficient air exchange and/or exhaust in work rooms. Avoid formation of dust cloud. Ensure adequate ventilation. Use personal protective equipment as detailed in Section 8. Handle and open container with care.
Storage : Store in a dry, cool, well-ventilated place.

SECTION 8 Exposure Controls / Personal Protection

EXPOSURE GUIDELINES

Hazardous Component	PEL	STEL	TLV	Other
Silica, respirable crystalline dust	0.1 mg/m ³ 8hr TWA (8 hour time weighted average) (CHAN)			
Respirable dust				4 mg/m ³ 8hr TWA
Occupational Exposure Standard for dust,				10mg/m ³ 8hr TWA

ENGINEERING MEASURES TO REDUCE EXPOSURE : LOCAL EXHAUST VENTILATION IS RECOMMENDED WHERE DUST IS LIKELY TO BE GENERATED FROM THE HANDLING OF DRY MATERIAL.

PERSONAL PROTECTIVE EQUIPMENT :

RESPIRATORY PROTECTION : DUST RESPIRATOR IF THE CONDITIONS ARE DUSTY.

EYE PROTECTION : GOGGLES OR FACE SHIELD.

HAND PROTECTION : IMPERVIOUS GLOVES

SKIN AND BODY PROTECTION : PROTECTIVE SUIT.

PROTECTIVE MEASURES : USE OF THE BASIC PRINCIPLES OF INDUSTRIAL HYGIENE WILL ENABLE THIS MATERIAL TO BE USED SAFELY.

RESPIRATORY WHEN THE PRODUCT IS SPRAYED OR HEATED WITHOUT ADEQUATE VENTILATION, AN APPROVED **MSHA/NIOSH** POSITIVE-PRESSURE, SUPPLIED-AIR RESPIRATOR MAY BE REQUIRED. AIR PURIFYING RESPIRATORS EQUIPPED WITH ORGANIC VAPOR CARTRIDGES AND A **HEPA (P100)** PARTICULATE FILTER MAY BE USED UNDER CERTAIN CONDITIONS WHEN A CARTRIDGE CHANGE-OUT SCHEDULE HAS BEEN DEVELOPED IN ACCORDANCE WITH THE **OSHA RESPIRATORY PROTECTION STANDARD (29 C.F.R. 1910.134)**

SECTION 9 Physical and Chemical Properties

Appearance	
Form	Granules/powder mix
Color	N/A
pH	~11-14
Melting/Freezing Temperature	N/A
Boiling Point	Not determined
Ignition Temperature	Higher than 93.3 deg C (200 deg F) Flash Point
Autoignition Temperature	Not applicable
Lower explosive limit; na	
Vapor Pressure	.not applicable
Vapor Density (air=1)	Not applicable
Specific Gravity (water=1 @39.2F)	n/A
Evaporation Rate (Bac=1)	N/P
Odor	None
Odor threshold	
Water Solubility	slight

SECTION 10 Stability and Reactivity

MATERIAL IS INERT AND STABLE.

CHROMIUM VI CONTENT IS NOT AN ISSUE FOR THIS MATERIAL - SHELF LIFE IS 6 MONTHS.

CONDITIONS TO AVOID : NOT APPLICABLE

MATERIALS TO AVOID : NOT APPLICABLE

HAZARDOUS DECOMPOSITION PRODUCTS : NONE.

SECTION 11 Toxicological Information

Inhalation: :May cause inflammation of the mucous membranes, an irritant to the respiratory tract at high concentrations.

Ingestion : The swallowing of small amounts is unlikely to cause any significant reaction. Larger doses may result in irritation of the gastro intestinal tract.

Eye irritation: Cements and hydrated lime are painful eye irritants. Mild exposure can cause soreness. Gross exposure or untreated mild exposures can lead to chemical burning and ulceration of the eye.

Skin Irritation: Cement and hydrated lime powder, especially in a water mix, may cause irritant contact dermatitis and or burns.

Long term toxicity :High repeated exposures in excess of the OES have been linked with rhinitis and coughing. Skin exposure has been linked to allergic (chromium VI) dermatitis.

Allergic dermatitis more commonly arises through contact with water mixtures than when dry.

Further information: Respirable crystalline silica dust may cause silicosis, a lung disease. Long term exposures to high levels of respirable crystalline silica can also lead to an increased risk of developing lung cancer.

SECTION 12 Ecological Information

Ecotoxicity: The addition of cement and hydrated lime to water will raise the pH and may therefore be toxic to aquatic life in some circumstances.

Mobility : The product is not volatile and insoluble in water, will accumulate in the ground.

Persistence and degradability: Mostly non-biodegradable. The hydrated lime will react with atmospheric and dissolved carbon dioxide to form calcium carbonate (e.g. chalk).

Bio accumulative potential : Not applicable.

Additional ecological information: High concentrations of lime and cement in water (>100 mg/l) may have a sterilizing effect in sewage works

SECTION 13 Disposal Considerations

Waste Disposal
 Unused Product/waste from cleaning etc.: Dispose of in accordance with local and national regulations.
 EWC Code: 08 01 99 (Not a hazardous waste)

Contaminated packaging: Contaminated packaging must not be disposed of as household waste.
 Not a hazardous waste.
 Use EWC Code: 150101 for paper, 150102 for plastic.

SECTION 14 Transport Information

Not classified as hazardous for transport.	
---	--

SECTION 15 Regulatory Information

Classification according to EEC directive: Irritant

R-phrases
 R41 : Risk of serious damage to eyes.

S-phrases
 S22 : Do not breathe dust.
 S26 : In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
 S28 : After contact with skin, wash immediately with plenty of water and soap.

S36/37/39 : Wear suitable protective clothing, gloves and eye/face protection.

Special provisions statement : None.

Hazardous component(s) which must be listed on the label: Cement/Hydrated Lime.

US EPA TSCA Status: All chemical ingredients are listed on the TSCA inventory.

Canada Domestic Substance List Status:
 All chemical ingredients are listed on the DSL

EC Directives: Dangerous Substances Directive, 67/548/EEC & adaptations.
 Dangerous Preparations Directive, 1999/45/EC.
 Safety Data Sheets Directive, 91/155/EEC and adaptations.

Statutory Instruments: Chemicals (Hazard Information & Packaging for Supply) Regs 2002.
 Control of Substances Hazardous to Health Regs 2002. Environmental Protection (Duty of Care) Regs. 1991. Codes of Practice
 Waste Management. The Duty of Care.
 Approved classification and labeling guide (Fifth edition). L131. The compilation of safety data sheets (Third edition).
 Guidance Notes Occupational Exposure Limits EH40
 CHIP for Everyone HSG(108)
 Construction Information Sheet No 26 (revision 2) CIS26(rev2) - Cement
 Construction Information Sheet No 36 (revision 1) CIS36(rev1) - Silica
 Chemical Hazard Alert Notice 35 – Respirable Crystalline Silica

SECTION 16 Other Information

Users of our products should take appropriate measures to ensure working practices are in accordance with the Control of Substances Hazardous to Health Regulations (COSHH).

Maximum exposure limits and Occupational Exposure Standards have been taken from EH40 Occupational Exposure Standards (from HSE Books).

Training Advice

Applicators need to be trained in:-
 Handling and hygiene associated with use of industrial chemicals.
 Correct mixing and application of the product.
 Correct cleaning and disposal methods.

HMIS Ratings

Health	:	2
Flammability	:	0
Reactivity	:	0

The product is intended for use by appropriately trained applicators in industrial situations. It is not suitable for use in home DIY applications, especially because of its hazardous nature and the protective measures required.

Notes - Do not use organic solvents for skin cleansing, it will lead to defatting of the skin, skin irritation and/or dermatitis. Some solvents can be absorbed through the skin. Beware of cross contamination where different products are in use in the same location. Take into account the Manual Handling regulations when dealing with the mixed product.

This safety data sheet is based on our present knowledge and experience and is intended to serve as a guide for safe handling of the product regarding to health and environmental aspects.

SECTION 1 Product and Company Information

PRODUCT NAME: Color Concentrate Rainbow Colors
GENERIC NAME: Plastic Colorant 24 Hour Emergency Number - N/A
Information Number: (877) 6 COLORS

DISTRIBUTOR: LSP Performance Resins
 124 Speer Road
 Chestertown, MD 21620

Comments: To the best of our knowledge, this Material Safety Data Sheet conforms to the requirements of US OSHA 29 CFR1910.1200, 91/155/ECC and Canadian Hazardous Products Act

SECTION 2 Hazards Identification

<p>Emergency Overview</p> <p>This product contains no hazardous ingredients as defined under the criteria of the federal OSHA Hazard Communication Standard 29 CFR 1910.1200. However, this MSDS contains information on the safe handling and proper use of the product. MSDS should be available for any person(s) in use of this product.</p> <p>Emergency Overview: Not expected to cause any adverse health effects when handled as recommended.</p>	<p>Potential Health Effects</p> <p>Inhalation: Not expected to be hazardous under standard conditions.</p> <p>Skin Contact: Not expected to be hazardous. Possible mild irritation.</p> <p>Eye Contact: Avoid eye contact. May cause eye irritation. Itching and redness after contact.</p> <p>Ingestion: Practically Non Toxic.</p> <p>Acute Effects: None Known.</p> <p>Chronic Effects: None Known.</p>		
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td style="width:30%;">Carcinogenicity: Not listed by NTP Not Listed by IARC Not Listed by OSHA</td> <td style="width:70%;"> Not listed Reproductive Effects : Not Available Teratogenic Effects: No evidence of mutagenetic effects </td> </tr> </table>	Carcinogenicity: Not listed by NTP Not Listed by IARC Not Listed by OSHA	Not listed Reproductive Effects : Not Available Teratogenic Effects: No evidence of mutagenetic effects	<p>Signs and Symptoms of Overexposure:</p>
Carcinogenicity: Not listed by NTP Not Listed by IARC Not Listed by OSHA	Not listed Reproductive Effects : Not Available Teratogenic Effects: No evidence of mutagenetic effects		

GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS

	Health	Environmental	Physical
Eye Irritant Skin Irritant, sensitizer Respiratory Irritant	None Known	Not Classified	Not Classified
Pictogram:			

SECTION 3 Composition / Information on Ingredients

Confidential Information (Only provided upon request, at which the manufacturer has the right to refuse to provide information). No ingredients are present within this product, based on our knowledge, that are classified as hazardous and required to be reported.

SECTION 4 First Aid Measures

Inhalation: Remove person to fresh air. If other respiratory symptoms develop, or person is breathing irregular, seek medical attention immediately.

Skin Contact: Immediately wash the skin with soap and water. Remove any contaminated clothing. If irritation, redness, itching or burning develops, seek medical attention immediately.

Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes. If irritation, redness, itching or burning develops, seek medical attention immediately.

Ingestion: Induce vomiting if person is conscious and alert. Seek medical attention.

Material Safety Data Sheet Color Concentrate

Effective Date: 01/01/2015

Previous Revision date: 00/00/0000

Date Printed: 3/19/2015

SECTION 5 Fire Fighting Measures

FLAMMABILITY: NO FIRE OR EXPLOSION HAZARDS KNOWN.
FLASH POINT: NOT APPLICABLE
AUTO IGNITION TEMP: NO DATA
EXTINGUISHING MEDIA: DRY CHEMICAL, CO2, WATER SPRAY OR REGULAR FOAM. AGENTS APPROVED FOR CLASS B HAZARDS.
SPECIAL EXPOSURE: REMOVE ALL PERSONS FROM THE AREA OF INCIDENT. ISOLATE THE SCENE AND ONLY ALLOW SUITABLE PERSONAL TO TAKE ACTION.
HAZARDOUS THERMAL: DECOMPOSE WITH EMISSION OF FUMES.
SPECIAL FIRE FIGHTING: EMPLOY TECHNIQUES THAT DO NOT CREATE DUSTS. FIRE- FIGHTERS SHOULD WEAR APPROPRIATE PROTECTIVE EQUIPMENT AND SELF-CONTAINED BREATHING APPARATUS WITH FULL FACE PIECE AND PROTECTIVE CLOTHING.

SECTION 6 Accidental Release Measures

Person Precautions: Only personal with proper training should take action, all others should evacuate the surrounding area.
Spills: Collection with shovels or vacuum and disposed of in properly labeled waste container. Clean area with detergent solutions. Provide adequate ventilations during clean-up.
Disposal Methods: Waste materials should be dumped or buried in an approved landfill, or incinerated in a suitable combustion chamber. Disposal must comply with all Federal, State and Local regulations.

SECTION 7 Handling and Storage

Storage: Store in cool, dry, well-ventilated area in sealed containers away from heat, open flames and oxidizing materials.
Handling: Use personal protective clothing. All persons in contain with this product should wash their hands and face before eating, drinking or smoking. See Section 8 for personal protection.

SECTION 8 Exposure Controls / Personal Protection

EXPOSURE GUIDELINES

PROTECTIVE CLOTHING: SYNTHETIC RUBBER GLOVES, APRON AND ARM COVERS TO AVOID SKIN CONTACT.
RESPIRATORY PROTECTION: IF NEEDED, USE MSHA-NIOSH APPROVED RESPIRATOR FOR DUST, MISTS AND FUMES. RESPIRATOR SHOULD BE CHOSEN BASED ON EXPOSURE LEVELS.
EYE PROTECTION: SAFETY GLASSES WITH SIDE SHIELDS ARE RECOMMENDED TO AVOID SPLASHES, MISTS OR DUSTS.
HYGIENE PROTECTION: AN EYE WASH STATION AND EMERGENCY SHOWER IN WORK AREA IS RECOMMENDED. APPROPRIATE TECHNIQUES SHOULD BE USED TO REMOVE ANY CONTAMINATED CLOTHING AND CLOTHING SHOULD BE WASHED BEFORE REUSING.
VENTILATIONS: ADEQUATE VENTILATIONS MUST BE PROVIDED. USE LOCAL EXHAUST TO KEEP EXPOSURE TO MINIMUM.

SECTION 9 Physical and Chemical Properties

Appearance	
Form	solid
Color	varies
pH	N/A
Melting/Freezing Temperature	N/A
Boiling Point	Not determined
Ignition Temperature	Not determined
Autoignition Temperature	Not applicable
Lower explosive limit; na	
Vapor Pressure	.not applicable
Vapor Density (air=1)	Not applicable
Specific Gravity (water=1 @39.2F)	N/A
Evaporation Rate (Bac=1)	N/P
Odor	None
Odor threshold	
Water Solubility	insoluble

SECTION 10 Stability and Reactivity

REACTIVITY: PRODUCT IS STABLE.

CONDITIONS TO AVOID: DIRECT HEATING, DIRT OR CHEMICAL CONTAMINATIONS.

INCOMPATIBLE MATERIALS: MAY REACT WITH STRONG OXIDIZING AGENTS.

HAZARDOUS

POLYMERIZATION: WILL NOT OCCUR UNDER NORMAL CONDITIONS.

HAZARDOUS

DECOMPOSITION: WILL NOT OCCUR UNDER NORMAL CONDITIONS. FIRE MAY PRODUCE IRRITATING, CORROSIVE AND/OR TOXIC GASES.

SECTION 11 Toxicological Information

United States: Acute Toxicity – Not Available
 Chronic Toxicity – Not Available
 Irritation/Corrosion – Not Available
 Sensitizer – Not Available
 Carcinogenicity – Not Available
 Mutagenicity – Not Available
 Teratogenicity – Not Available
 Reproductive Toxicity – Not Available

SECTION 12 Ecological Information

Biodegradability: Not determined

Aquatic Ecotoxicity: Not determined

Specific ecotoxicological data is not available for this product. Organic pigments and solvent dyes, in general, are not expected to be toxic to fish because of their negligible water solubility; thus, they are not readily bioavailability.

SECTION 13 Disposal Considerations

Waste Disposal

Waste should be avoided or minimized whenever possible. Containers or lines may contain residues after being emptied. Waste materials should be dumped or buried in an approved landfill, or incinerated in a suitable combustion chamber. Avoid areas that product could be in contact with soil, waterways, drains and sewers. Disposal must comply with all Federal, State and Local regulations.

SECTION 14 Transport Information	
Not classified as hazardous for transport.	DOT Classification: Not Regulated TDG Classification: Not Regulated Mexico Classification: Not Regulated UN/PIN Number: Not Regulated IATA-DGR Class: Not Regulated IMDG Class: Not Regulated ADR/RID Class: Not Regulated

SECTION 15 Regulatory Information

U.S. Federal Regulations:

HCS Classification: Not regulated.

TSCA 8b: All ingredients are listed or exempted.

SARA 302/304/311/312 Extremely hazardous substances:
 No products were found.

Clean Water Act (CWA) 307/311:
 No products were found.

CONEG: This product meets coneg regulations.

Clean Air Act (CCA) 112:
 This product neither contains nor is manufactured with ozone depleting substances.
 DEA List I & II Chemicals: Not Listed

OHSA Status:
 Not hazardous under criteria of federal hazardous communications standard 29 CFR 1910.1200.
 California Prop 65:
 To the best of our knowledge, this product does not contain any of the listed chemicals, which the state of California has found to cause cancer, birth defects or other reproductive harm.
 EU Regulations:
 Product is not classified or registered under EU legislation, but components within this product are authorized in accordance with the requirements of Commission Regulation (EU) No 1282/2011.
 International Regulations:
 Australia, China, Japan, Korea, New Zealand, Philippines:
 Not Determined

SECTION 16 Other Information

HMIS Rating:	Health	-1	
	Flammability	-1	
	Reactivity	-0	
	Personal Protection	-E	

Other Precautions: Do not transfer to unmarked containers. Follow DOT regulations. This product is not regulated as hazardous material by DOT.

Revision Date: 10/1/2013
 Revised to be in compliance with new GHS regulations due by 12/1/2013.

DISCLAIMER:
 The above information is provided on the data available to us and believed to be true and accurate. The information contained herein is offered in good faith and no warranty, expressed or implied, are made regarding the accuracy of this data since conditions or use is beyond our control. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Rainbow Colors, Inc. assumes no responsibilities for the use of handling of this product.