

DIVISION _____

Specification Section # _____

Broomstow

Wall mounted broom and mop hanger designed to allow cleaning equipment to be stored off the floor and away from the wall.

Single piece frame of clear anodized extruded 6061-T6 aluminum alloy, Federal Specification QQA 200/8.

Frame dimensions are ¼" thick x 4" wide w/ 1/8" radius top and bottom edges and ¾" radius bends at each end to position outside face of frame 1¾" from wall surface.

Configuration is such so as to eliminate hollows and to minimize lateral flat surfaces which may collect dirt, dust, debris, etc.

Main frame for a single position cleat is 14" long, increasing by 5" for each additional cleat.

Specify size as follows:

BS-1: 1 cleat @ 14"

BS-2: 2 cleats @ 19"

BS-3: 3 cleats @ 24"

BS-4: 4 cleats @ 29"

BS-5: 5 cleats @ 34"

BS-6: 6 cleats @ 39"

BS-7: 7 cleats @ 44"

BS-8: 8 cleats @ 49"

Frame will have (4) 5/16" mounting holes, (2) at each end of frame. Stainless steel mounting hardware to be specified by manufacturer depending on wall type.

Cleat is black, high-impact plastic with dense foam covered, gravity/pinch type cleat mounted to frame with stainless steel hardware.