

<i>Glasswall FR Coating System</i>		
Proper Name	Use within System	Name on General MSDS List
WRP850 and WHP850	Epoxy resin and hardener for coating system	WRP850 and WHP850
Fiberglass 3373	Fiberglass reinforcing mat for wall system	Fiberglass

SeamTek® Epoxy Glasswall-FR

1. Product Description

Basic use

SeamTek® Glasswall resin is a two component 100% solids, low-odor, low viscosity, low VOC resin that chemically cures to form a rigid and highly abrasion resistant binder for high performance interior coating systems. It has been specifically designed to exhibit excellent flow characteristics, air release, and workable viscosity.

In the FR or fiberglass reinforced system, 5.6 oz. fiberglass mat is incorporated in the coatings to produce a 30 – 35 mil thick reinforced coating system. The FR system adds structural integrity to gyp board walls, yields a smooth finish and adds overall sustainability to the wall coatings that lasts longer than conventional coatings.

Features and benefits include:

- No amine blush – no frosting
- Self leveling
- Low foaming
- Excellent adhesion to concrete
- Good workability – easy to spread
- 100% solids – solvent free
- Low VOC
- Low odor
- Low flammability

The LSP SeamTek® systems are composed of resins and aggregates which utilize the best available technology for safety and performance. All products and systems are extensively field tested prior to use on SeamTek® projects.

Composition and Materials

SeamTek® Pigmented Epoxy Resin WP850 is a chemical curing, two component, 100 % solids epoxy coating.

Sizes

The binder resin and hardener are packaged in 5 U.S. gallon (18.9 liter) pails.

Limitations

SeamTek® WP850 must not be used to bridge moving cracks or joints. Non-moving cracks or joints that must be over coated require rigid repairs. See LSP Technical Manual System Specifications for details. Surface or air

temperature must be between 65°F minimum and 80°F maximum and relative humidity below 80%. Lower temperatures will extend cure time and higher temperatures will reduce pot and work life.

Storage and Handling

Because WP850 has a flash point above 200°F (93°C), transportation, storage and handling are less restricted. The binder resin is freeze/thaw stable, which allows flexibility in storage of the product, on or off site.

Product Health and Safety Information

Refer to container labels and Material Safety Data Sheets available from LSP for health, safety and environmental information. If necessary, call LSP at (800) 638-9874.

Applicable Standards

LSP SeamTek® Pigmented Epoxy Resin WP850 has been tested in accordance with American Society for Testing and Materials (ASTM) methods. Refer to Table 1 on page 1 for more information. SR101 can be used as a floor coating in food processing areas and other similar applications. The USDA and FDA no longer regulates coatings used on floors, walls, and ceilings in food process areas, since the surfaces are not intended for food contact.

Surface Preparatory Work

Preparatory work must be done in accordance with

Table 1 Typical Physical Properties

Property	Measuring Standards and Conditions	Results Part A/Part B
Specific Gravity	ASTM D 70, Fisher #3-247 pycnometer	1.07
Weight +/- 0.4 lbs./gal.	ASTM E 201	9.2 lbs./gal.
Non-volatile Content	ASTM D 1353, 18 hrs. at 200°F (93°C)	100%
Viscosity, cps	ASTM D 1475 77°F (25°C)	Self-leveling 1200-1500
Flash Point, TCC minimum	Seta Flash	Greater than 200°F (93°C)
Solvent Odor	ASTM D 1296	Extremely low
Pot Life		50 to 60 minutes at 72°F (22°C) & 50% R.H.

procedures described in LSP Technical Manual.

Mixing

Caution, Containers used to measure WP850 resin and Harder must be marked appropriately and only used to measure the indicated component. Container used to mix both resin and hardener must be cleaned or changed after mixing each batch to avoid residual material affecting viscosity and cure rates.

Measure both parts by volume 2 to 1 into a plastic marked containers. Pour resin and hardener into a separate container and agitate using a jiffy paddle and low speed drill (400-600 rpm). Agitate for 2 minutes, and then scrape sides of container and mix for an additional minute. Avoid generating air bubbles and foam. Consider mixing small batches to reduce potential waste. To avoid exothermic reaction in mixing container, do not let mixed components sit in container. Mix only the amount of material that can be applied and finished in 25 minutes. Spread or finish material according to application instructions contained in LSP Technical Manual.

3. Warranty

LSP Performance Resin Systems are installed by LSP Associate Contractors and are available with the LSP Single Source Limited Warranty for Labor and Material. This Product Data Sheet is for your information and is not a contract nor a product warranty. Your installation contract is provided by your LSP Associate Contractor. LSP's warranty to you is made solely in the LSP Single Source Limited Warranty for Labor and Material. Contact your Associate Contractor for the specific warranty document.

4. Maintenance

SeamTek® Systems are hard seamless surfaces that will provide years of life with little maintenance. For more detailed maintenance instructions, please request LSP Floor Maintenance Instructions. Periodic inspections by your LSP Associate Contractor are recommended to discuss ways to extend the life of the floor care.

5. Technical Service

Call your LSP representative for assistance.

Table 2 – Typical Performance Properties

Property	Measuring Standards and Conditions	Binder Resin Results Only See Note 1 below
Drying time	ASTM D 1475 77°F (25°C)	To Touch: 8 to 12 hrs., max. To complete: 24 hrs. max.
Hardness (indentation)	ASTM D 2240 Rex D Model 1700	65-70 resin only 80-85 with aggregate
Elongation	ASTM D 638	Less than 0.1%
Tensile Strength	ASTM D 638	4500 psi (31 MPa)
Water Absorption	ASTM D 570-95	Less than 0.2%
Indentation Resistance	Mil. Std. D-3134	Zero
Water Vapor Transmission	ASTM E 96-94	Less than 0.10 U.S. perms
Weathering Resistance	ASTM G 26 Type B, BH, 300 hrs	Slight Yellowing
Abrasion Resistance	ASTM C 501, CS-17 Wheel, 1000 rev. with 1000 gram weight	Less than 0.1 grams weight loss
Bond Strength to Concrete	ASTM D 4541	350 to 500 psi (2.4 to 3.4 MPa) epoxy holder fails
Electrical Conductivity		Non conductive
Flammability	ASTM D 635	Self-Extinguishing

1. For additional performance properties for binder resin with aggregate added (ie. Tensile Strength, Flexural Strength, Flexural Modulus, Compressive Strength, Coefficient of Linear Expansion, etc.) refer to LSP technical manual for specific system(s) selected.



Safety Data Sheet

Section 1: PRODUCT AND COMPANY IDENTIFICATION

SDS Identification: HexForce™ F3 and F16 Finish

SDS Number: 439-3227-4055-316G-20 **Date:** December 1, 2009 **Page:** 1 of 7

Supersedes SDS: 439-3227-3160-0000-19

Manufacturer:

Hexcel®
11711 Dublin Blvd.
Dublin, CA 94568

Emergency Telephone Number:

800-433-5072 (24-Hour) Hexcel®

Information Telephone Number:

830-379-1580 (Normal Business Hours-CT)

Product Identification: HexForce™ F3 and F16 Finish: Fiberglass

Chemical Family: Woven Fiberglass Fabric using E-Glass or S2 Glass Fibers with a Chromium (Cr³⁺) Methacrylate Finish applied.

Section 2: COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS® Number	% by Weight	OSHA (PEL)	ACGIH® (TLV®)
Fiberglass fiber, synthetic, vitreous, continuous filament	65997-17-3	98.8-99.9	15 mg/m ³ (Total) 5 mg/m ³ (Respirable)	5 mg/m ³ (Inhalable) 1 f/cc (Respirable)

This product is not classified as a Hazardous Chemical as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200

Where specific exposure limits for component dusts are not established, the levels provided for (Total/Inhalable) dust and (Respirable) fraction reflect the classification of Particulate Not Otherwise Regulated (PNOR) by OSHA or Classified (PNOC) by ACGIH®.

Section 3: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

Appearance and Odor:

White fibers, with a greenish tint, woven into fabrics of varying weight, width and thickness, depending on the style, with a finish applied, with no distinctive odor. There may be a sealant applied to the edges of slit fabrics (less-than-full-width) to prevent fibers unwinding during use.

Statement of Hazard:

Warning! May cause temporary mechanical irritation of the eyes, skin or upper respiratory tract.

Dust or particulate from machining, grinding or sawing the cured product may cause skin, eye and upper respiratory irritation and possible dermatitis.

Section 3: HAZARDS IDENTIFICATION (Continued)

Primary Routes of Exposure:

Eyes--Yes Skin--Yes Inhalation--Yes Ingestion--No

HMIS® Rating:

Health--1 Flammability--0 Reactivity--0 Special--None

Potential Health Effects:

Eye: Contact may cause mechanical irritation to the eyes. Dust or particulate from machining, grinding or sawing the cured product may cause mechanical irritation.

Skin: Contact may cause mechanical irritation to the skin and possible dermatitis at clothing contact pressure points such as cuffs or collars. Dust or particulate from machining, grinding or sawing the cured product may cause mechanical irritation and possible dermatitis.

Inhalation: May cause mechanical irritation to the upper respiratory tract. Dust or particulate from machining, grinding or sawing the cured product may cause mechanical irritation to the upper respiratory tract.

Ingestion: Very unlikely. If a large amount of the product or the dust or particulate from the machining, grinding or sawing the cured is swallowed, seek medical attention immediately.

Medical Conditions Aggravated By Exposure: Preexisting conditions such as respiratory or skin disorders may be aggravated by exposure to the product or to the dust or particulate from machining, grinding or sawing the cured product.

Carcinogenic Information: None of the finish components present in this material at concentrations equal to or greater than 0.1 % are listed or regulated by NTP, OSHA or ACGIH® as a carcinogen. Glass filament is listed by IARC as Group 3 (not classifiable as to a human carcinogen).

Other:

	OSHA (PEL)	ACGIH® (TLV®)
Exposure limits for cured product dust as [Particulate Not Otherwise Regulated (PNOR) by OSHA or Classified (PNOC) by ACGIH®]:	15 mg/m ³ (Total) 5 mg/m ³ (Respirable)	10 mg/m ³ (Inhalable) 3 mg/m ³ (Respirable)

Section 4: FIRST AID MEASURES

Eye: In case of contact with the product or the cured product dust or particulate, immediately flush eyes with large amounts of water for at least 15 minutes, keeping the eyelids open. Get medical attention immediately.

Skin: In case of contact with the product or the cured product dust or particulate, immediately wash skin with mild soap and room temperature to cool running water. Use a washcloth to help remove the fibers. To avoid further irritation, do not rub or scratch irritated areas. Rubbing or scratching may force fibers into the skin. Get medical attention immediately if the irritation persists.

Section 4: FIRST AID MEASURES (Continued)

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, qualified personnel may administer oxygen. Get medical attention immediately.

Ingestion: Ingestion of the product or the dust or particulate from it is unlikely. If swallowed, get medical attention immediately.

Section 5: FIRE FIGHTING MEASURES

Flash Point Method of Determination: Not determined

Means of Extinction: Use water spray, dry chemical or CO₂ to extinguish fires.

Special Fire Hazards: Avoid exposure through use of a self-contained, positive-pressure breathing apparatus.

Section 6: ACCIDENTAL RELEASE MEASURES

Procedures in case of Accidental Release or Leakage: Avoid contact with skin, eyes or clothing (See Section 8). Clean up material, put into a suitable container and dispose of properly (See Section 13).

Section 7: HANDLING AND STORAGE

Precautions to be taken in Handling and Storage: Store in a cool, dry place. Maintain sealed against contamination from dirt and moisture.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye/Face Protection: Avoid eye contact. Wear coverall goggles, as necessary, to prevent irritation, if airborne dust, fibers or particulate are present. Wear safety glasses with side shields, as necessary, if airborne dust, fibers or particulate are present when machining, grinding or sawing the cured product.

Skin Protection: Wear protective clothing such as a loose fitting, long sleeved shirt that covers to the base of the neck, long pants and gloves, as necessary, to prevent irritation. Skin irritation is known to occur primarily at pressure points such as around the neck, wrist, waist and between the fingers.

Respiratory Protection: Not ordinarily required. If sufficient dust, fibers or particulate are generated during use of the product or when machining, grinding or sawing the cured product, use a NIOSH approved dust respirator.

Ventilation: Use local exhaust sufficient to control dust, fibers or particulate generated. If an exhaust ventilation is not available or is inadequate, use a NIOSH approved dust respirator.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (Continued)

General Hygiene Recommendations: Before eating, drinking, smoking or using toilet facilities, wash face and hands thoroughly with soap and water. Remove any contaminated clothing and launder before reuse. Use vacuum equipment to remove fibers, dust or particulate from clothing and work areas. Compressed air is not recommended.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance and Odor... White fibers, with a greenish tint, woven into fabrics of varying weight, width and thickness, depending on the style, with a finish applied, with no distinctive odor. There may be a sealant applied to the edges of slit (less-than-full-width) fabrics to prevent fibers unwinding during use.

Melting Point (°F/°C)..... >1292°F/>700°C

Specific Gravity (Water=1)..... 2.60

pH of Undiluted Product.....Not determined

Volatile [Percent (%) by Weight]..... 0

Percent (%) VOC.....Same as the % Volatile Content

Solubility in Water..... Insoluble

Section 10: STABILITY AND REACTIVITY

Stability: Stable under proper handling and storage conditions

Incompatible Materials: None

Products evolved from Heat of Combustion or Decomposition: The products of combustion and decomposition depend on other materials present in the fire and the actual conditions of the fire. Burning will decompose the finish and release carbon, nitrogen and silicon oxides, water, ammonia, hydrogen chloride, traces of incompletely burned carbon products and other unidentified gases and vapors that may be toxic. Avoid inhalation.

Hazardous Polymerization: Will not occur under proper conditions of use. Rapid heating of the product in bulk may produce an uncontrolled exothermic reaction that may char and decompose the finish, generating unidentified gases and vapors that may be toxic. Avoid inhalation.

Section 11: TOXICOLOGICAL INFORMATION

Component Toxicity Data:

Median Lethal Dose (Species):

Oral (LD₅₀)...Not determined

Inhalation (LC₅₀)...Not determined

Dermal (LD₅₀)...Not determined

Irritation Index, Estimation of Irritation (Species):

Skin...Not determined

Eye...Not determined

Inhalation...Not determined

Section 12: ECOLOGICAL INFORMATION

No ecological data has been determined.

Section 13: DISPOSAL CONSIDERATIONS

Waste Disposal Methods: Material for disposal should be placed in appropriate sealed containers to avoid potential human and environmental exposure. It is the responsibility of the generator to comply with all federal, state, provincial and local laws and regulations. We recommend that you contact an appropriate waste disposal contractor and environmental agency for relevant laws and regulations. Under the U.S., Resource Conservation and Recovery Act (RCRA), it is the responsibility of the user of the product to determine at the time of disposal, whether the product meets relevant waste classification.

Section 14: TRANSPORT INFORMATION

DOT:

Proper Shipping Name..... Not regulated
Hazard Class..... Not regulated
Identification Number.....Not regulated
Packing Group.....Not regulated
Label Required..... None

Section 15: REGULATORY INFORMATION

SARA Title III:

Section 302/304 Extremely Hazardous Substance:
None

Section 311 Hazardous Categorization:
None

Section 313 Toxic Chemicals:
None

CERCLA Section 102(A) and Hazardous Substance:
None

RCRA Information: Currently, this product is not listed in federal hazardous waste regulations 40 CFR, Part 261.33, paragraphs (e) or (f), i.e. chemical products that are considered hazardous if they become wastes. State or local hazardous waste regulations may also apply if they are different from the federal regulation. It is the responsibility of the user of the product to determine at the time of disposal, whether the product meets relevant waste classification and to assure proper disposal.

WHMIS (Canada):

Classification:
None

Section 15: REGULATORY INFORMATION (Continued)

WHMIS (Canada) (continued):

"This product has been classified in accordance with hazard criteria of the "Controlled Products Regulations" and this SDS contains all the information required by the "Controlled Products Regulations."

Ingredient Disclosure List:

None

U.S., EPA and TSCA Information: This product is an article as defined by TSCA and is not required to be listed in the TSCA Inventory.

Ozone Depletion Information: This product does not contain or is not manufactured with ozone depleting substances as identified in Title VI, Clean Air Act "Stratospheric Ozone"

Section 16: OTHER INFORMATION

Special Precautions: None

Explanation and Disclaimer: Wherever such words or phrases as "hazardous," "toxic," "carcinogen," etc. appear herein, they are used as defined or described under state employee right-to-know laws, Federal OSHA laws or the direct sources for these laws such as the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), etc. The use of such words or phrases should not be taken to mean that we deem or imply any substance or exposure to be toxic, hazardous or otherwise harmful. **Any exposure can only be understood within the entire context of its occurrence, which includes such factors as the substance's characteristics as defined in the SDS, amount and duration of exposures, other chemicals present and preexisting individual differences in response to the exposure.**

The data provided in this SDS is based on the information received from our raw material suppliers and other sources believed to be reliable. We are supplying you this data solely in compliance with the Federal OSHA Hazard Communication Standard, 29 CFR 1910.1200 and other Federal and state laws as described in Section 15: Regulatory Information.

The information contained in this SDS is proprietary and confidential to Hexcel Corporation. This SDS and the information in it are not to be used for purposes other than compliance with the Federal OSHA Hazard Communication Standard. If you have received this SDS from any other source than Hexcel Corporation or its authorized agent, the information contained in it may have been modified from the original document and it may not be the most current revision.

Liability, if any, for use of this product is limited to the terms contained in our sale terms and conditions. We do not in any way warrant (expressed or implied, including any implied warranty for merchantability or fitness for a particular purpose) the data contained or the product described in this SDS. Additionally, we do not warrant that the product will not infringe any patent or other proprietary or property rights of others.

Section 16: OTHER INFORMATION (Continued)

Prepared by: Darryl Ong,
Hexcel Corporate Safety and Health,
Senior Product Safety Information Specialist

Revision History:

12/18/09 update description

01/28/09 deleted "CS" nomenclature

10/01/07 changed information telephone number and updated contacts

03/19/07 deleted Prop 65, product is not manufactured in Calif.

SECTION 1 Product and Company Information

PRODUCT NAME: SeamTek® Wall Coating Hardener WHP850 Chemtrec
GENERIC NAME: Cycloaliphatic diamine epoxy hardener 24 Hour Emergency Number 1-800-424-9300
Information Number: 1-800-666-6216

DISTRIBUTOR: LSP Performance Resins
 124 Speer Road
 Chestertown, MD 21620

Comments: To the best of our knowledge, this Material Safety Data Sheet conforms to the requirements of US OSHA 29 CFR1910.1200, 91/155/ECC and Canadian Hazardous Products Act

SECTION 2 Hazards Identification

<p>Emergency Overview</p> <p>OSHA Hazardous</p> <p>Target Organ Effect: Skin Sensitizer, Irritant</p> <p>Target Organs: Respiratory, eyes, Skin</p> <p>Physical Appearance: Viscous liquid</p> <p>Immediate Concerns: Skin Irritation</p>	<p>Potential Health Effects</p> <p>Skin: Will cause irritation and dermatitis, repeated overexposure will cause dermatitis and sensitization. Sensitized persons may experience rapid irritation of skin upon exposure.</p> <p>Inhalation and Ingestion: Irritation to system</p>
<p>Carcinogenicity: Not listed by NTP Not Listed by IARC Not Listed by OSHA</p>	<p>Reproductive Toxicity Reproductive Effects : Not Available Teratogenic Effects: Not Available</p>
<p>Signs and Symptoms of Overexposure: Irritation of Skin</p> <p>Medical Conditions Aggravated: Allergy, Skin Disorders</p>	

GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS

Health	Environmental	Physical
Acute Toxicity, Oral Skin Irritant Serious Eye Damage Skin Sensitization	Category 5 Category 2 Category 1 Category 1	Not Classified

Pictogram:



Signal Word Danger

Hazard Statements	Precautionary Statements
H303 May be harmful if swallowed	P280 Wear protective gloves/protective clothing/eye protection/face protection P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
H315 Causes skin irritation	
H317 May cause an allergic skin reaction	
H318 Causes serious eye damage	

SECTION 3 Composition / Information on Ingredients

Chemical Name	CAS	Wt%
Benzyl alcohol	100-51-6	25-40
Cycloaliphatic Diamine	2855-13-2	18-35
Polyoxypropylenediamine	9046-10-0	15-30
Propylene Glycol Monomethyl Ether (PM)	107-98-2	10-20
1,5 pentanediamine, 2 methyl	15520-10-2	1-5
Amorphous Silicon Dioxide	7631-86-9	2-6
Salicylic acid	69-72-7	3-10

SECTION 4 First Aid Measures

EYE CONTACT: Get medical attention immediately. Immediately flush eyes gently with large amounts of water, holding lids open for at least 20-30 minutes, retracting eyelids often. Check for, and remove contact lenses.

SKIN CONTACT: Get medical attention immediately. Flush contaminated skin with plenty of WATER. Do NOT wash with solvents. Wash contaminated clothing thoroughly with water before removing it or wear gloves. Continue to rinse for at least 10 minutes. May cause irritation and allergic reaction. Seek medical advice if irritation develops or persists.

INHALATION: Move exposed person to fresh air. Get medical attention immediately. If it is suspected that fumes are still present, the rescuer should wear an appropriate make of self contained breathing apparatus. Keep person warm and at rest. If not breathing or breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing air to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway

INGESTION: Get medical attention immediately. Wash out mouth with water. Move exposed person to fresh air. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.

Advice to physicians: Symptomatic and supportive therapy as needed. May aggravate skin conditions.

SECTION 5 Fire Fighting Measures

Conditions of Flammability

Not flammable or combustible

Suitable Extinguishing Media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Hazardous Decomposition Products

Hazardous decomposition products formed under fire conditions – Carbon Oxides

Fire Fighting Instructions

Do not enter fire area without proper protection. Wear self contained breathing apparatus (pressure-demand MSHA/NIOSH) approved or equivalent. See Section 10 - decomposition products possible. Fight fire from safe distance/protected location. Heat/impurities may increase temperature/build pressure/rupture closed containers, spreading fire, increasing risk of burns/injuries. Use water spray/fog for cooling.

SECTION 6 Accidental Release Measures

Personal Precautions

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).

Environmental Precautions

Avoid dispersal of spill material and runoff and contact with soil, waterways, drains and sewers. Notify authorities of any releases to sewers, soils, waterways or air.

Methods and Materials for Containment and Cleaning Up

Stop the leak if it can be done without risk. Move containers from the spill area. Prevent entry into sewers, water ways or soils. Contain and collect spillage with non-combustible, absorbent material such as sand, earth, vermiculite or diatomaceous earth. Place in container for disposal according to local regulations via a licensed waste disposal contractor. Contaminated absorbent materials may pose the same hazards as the spilled product. See section 1 for emergency contact information and section 13 for waste disposal.

SECTION 7 Handling and Storage

Precautions for Safe Handling Can cause skin and eye irritation and allergic skin reaction.

Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Conditions for Safe Storage

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

SECTION 8 Exposure Controls / Personal Protection

EXPOSURE GUIDELINES

Hazardous Component	PEL	STEL	TLV	Other
Benzyl alcohol	NE	NE	NE	NE
Cycloaliphatic Diamine	NE	NE	NE	NE
Polyoxypropylenediamine	NE	NE	NE	NE
Propylene Glycol Monomethyl Ether (PM)	100 ppm	NE	100 ppm	NE
1,5 pentanediamine, 2 methyl	NE	NE	NE	NE
Amorphous Silicon Dioxide	NE	NE	NE	NE
Salicylic acid	NE	NE	NE	NE

ENGINEERING CONTROLS Use local exhaust ventilation to maintain airborne concentrations below exposure limits. Respiratory protection may be required in addition to general room ventilation.

PERSONAL PROTECTIVE EQUIPMENT Use a properly fitted, air-purifying or air supplied respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards or the product and the safe working limits of the selected respirator.

EYE PROTECTION Eye protection such as chemical splash goggles and/or face shield must be worn when possibility exists for eye contact due to splashing or spraying liquid, airborne particles or vapor. Contact lenses should not be worn.

SKIN AND BODY PROTECTION When skin contact is possible, protective clothing including gloves, apron, sleeves, boots, head and face protection should be worn. Gloves should be impervious neoprene or rubber. Use of barrier cream is recommended. Clean equipment thoroughly after each use. Discard contaminated leather shoes and canvas sneakers.

OTHER HYGIENIC PRACTICES Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

OTHER WORK PRACTICES Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet facilities. Promptly remove soiled clothing and wash thoroughly before reuse. Shower after work using plenty of soap and water.

SECTION 9 Physical and Chemical Properties

Appearance	
Form	Liquid
Color	Slightly hazy
pH	Not available
Melting/Freezing Temperature	N/A
Boiling Point	N/A
Flash Point	100 F
Ignition Temperature	Not available
Autoignition Temperature	Not available
Lower explosive limit; na	Upper explosive limit: na
Vapor Pressure	12.6 mm Hg
Vapor Density (air=1)	Not available
Specific Gravity (water=1 @39.2F)	>1.01
Evaporation Rate (Bac=1)	None
Odor	amine
Odor threshold	Not available

SECTION 10 Stability and Reactivity

Chemical Stability

Stable under recommended storage conditions

Possibility of Hazardous Reactions

No data available

Conditions to Avoid

Avoid strong acids, bases in bulk and elevated temperatures

Materials to Avoid

Reactive or incompatible with: acids, oxidizers, amines

Hazardous Decomposition Products

Decomposition products formed under fire conditions may include: Carbon oxides, Nitrogen oxides, Aldehydes.

SECTION 11 Toxicological Information

Acute Toxicity

Oral LD50	Rat > 4000 mg/kg.
Dermal LD50	Rabbit 20,000 mg/kg
Inhalation LC50	No data available

Carcinogenicity

IARC: No component of this product presents at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC

Skin Corrosion/Irritation

Skin	Irritant
------	----------

ACGIH: No component of this product presents at levels greater than or equal to 0.1% is identified as carcinogen or potential carcinogen by ACGIH

Serious Eye Damage/Eye Irritation

Eye	Irritant
Eyes	Rabbit
Severe eye irritation – 24 H	

NTP: No component of this product presents at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP

Respiratory or Skin Sensitization

May cause skin or respiratory sensitization

Mutagenicity

Mouse	Skin
Carcinogenic by RTECS Criteria	
liver, ovarian, thyroid	

SECTION 12 Ecological Information

Aquatic Ecotoxicity

No data available

Biodegradability

Persistent	Not readily biodegradable
------------	---------------------------

Mobility in soil

No data available

SECTION 13 Disposal Considerations

Waste Disposal

The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residuals. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 1 Product and Company Information

PRODUCT NAME: SeamTek® Wall Coating Resin WRP850 (all colors) Chemtrec
GENERIC NAME: Pigmented Epoxy Resin 24 Hour Emergency Number 1-800-424-9300
Information Number: 1-800-666-6216

DISTRIBUTOR: LSP Performance Resins
124 Speer Road
Chestertown, MD 21620

Comments: To the best of our knowledge, this Material Safety Data Sheet conforms to the requirements of US OSHA 29 CFR1910.1200, 91/155/ECC and Canadian Hazardous Products Act

SECTION 2 Hazards Identification

Emergency Overview OSHA Hazardous Target Organ Effect: Skin Sensitizer, Irritant Target Organs: Respiratory, eyes, Skin Physical Appearance: Viscous liquid Immediate Concerns: Skin Irritation		Potential Health Effects Skin: Will cause irritation and dermatitis, repeated overexposure will cause dermatitis and sensitization. Sensitized persons may experience rapid irritation of skin upon exposure. Inhalation and Ingestion: Irritation to system
Carcinogenicity: Not listed by NTP Not Listed by IARC Not Listed by OSHA	Reproductive Toxicity Reproductive Effects : Not Available Teratogenic Effects: Not Available	Signs and Symptoms of Overexposure: Irritation of Skin Medical Conditions Aggravated: Allergy, Skin Disorders

GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS

Health	Environmental	Physical
Acute Toxicity, Oral Skin Irritant Serious Eye Damage Skin Sensitization	Category 5 Category 2 Category 1 Category 1	Not Classified Not Classified

Pictogram: 

Signal Word Danger

Hazard Statements	Precautionary Statements
H303 May be harmful if swallowed	P280 Wear protective gloves/protective clothing/eye protection/face protection P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
H315 Causes skin irritation	
H317 May cause an allergic skin reaction	
H318 Causes serious eye damage	

SECTION 3 Composition / Information on Ingredients

Chemical Name	CAS	Wt%
Diglycidyl ether bisphenol A epoxy resin	25085-99-8	45-65
Aliphatic glycidyl ether diluents	68609-97-2	4-10
Rutile titanium dioxide	13463-67-7	4-30
Calcium carbonate	1317-65-3	3-8
Aluminum silicate	1332-58-7	0-2
Barium sulfate	7727-43-7	3-20
Inorganic iron oxides	1309-37-1	4-20
Chromium III trivalent chromum	1308-38-9	4-20

SECTION 4 First Aid Measures

EYE CONTACT: Get medical attention immediately. Immediately flush eyes gently with large amounts of water, holding lids open for at least 20-30 minutes, retracting eyelids often. Check for, and remove contact lenses.

SKIN CONTACT: Get medical attention immediately. Flush contaminated skin with plenty of WATER. Do NOT wash with solvents. Wash contaminated clothing thoroughly with water before removing it or wear gloves. Continue to rinse for at least 10 minutes. May cause irritation and allergic reaction. Seek medical advice if irritation develops or persists.

INHALATION: Move exposed person to fresh air. Get medical attention immediately. If it is suspected that fumes are still present, the rescuer should wear an appropriate make of self contained breathing apparatus. Keep person warm and at rest. If not breathing or breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing air to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway

INGESTION: Get medical attention immediately. Wash out mouth with water. Move exposed person to fresh air. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.

Advice to physicians: Symptomatic and supportive therapy as needed. May aggravate skin conditions.

SECTION 5 Fire Fighting Measures

Conditions of Flammability

Not flammable or combustible

Suitable Extinguishing Media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Hazardous Decomposition Products

Hazardous decomposition products formed under fire conditions – Carbon Oxides

Fire Fighting Instructions

Do not enter fire area without proper protection. Wear self contained breathing apparatus (pressure-demand MSHA/NIOSH) approved or equivalent. See Section 10 - decomposition products possible. Fight fire from safe distance/protected location. Heat/impurities may increase temperature/build pressure/rupture closed containers, spreading fire, increasing risk of burns/injuries. Use water spray/fog for cooling.

SECTION 6 Accidental Release Measures

Personal Precautions

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).

Environmental Precautions

Avoid dispersal of spill material and runoff and contact with soil, waterways, drains and sewers. Notify authorities of any releases to sewers, soils, waterways or air.

Methods and Materials for Containment and Cleaning Up

Stop the leak if it can be done without risk. Move containers from the spill area. Prevent entry into sewers, water ways or soils. Contain and collect spillage with non-combustible, absorbent material such as sand, earth, vermiculite or diatomaceous earth. Place in container for disposal according to local regulations via a licensed waste disposal contractor. Contaminated absorbent materials may pose the same hazards as the spilled product. See section 1 for emergency contact information and section 13 for waste disposal.

SECTION 7 Handling and Storage

Precautions for Safe Handling Can cause skin and eye irritation and allergic skin reaction.

Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Conditions for Safe Storage

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

SECTION 8 Exposure Controls / Personal Protection

EXPOSURE GUIDELINES

Hazardous Component	PEL	STEL	TLV	Other
Diglycidyl ether bisphenol A epoxy resin	NE	NE	NE	NE
Aliphatic glycidyl ether diluents	NE	NE	NE	NE
Rutile titanium dioxide	10 mg/m3	NE	10 mg/m3	NE
Calcium carbonate	10 mg/m3	NE	10 mg/m3	NE
Aluminum silicate	10 mg/m3	NE	10 mg/m3	NE
Barium sulfate	10 mg/m3	NE	10 mg/m3	NE
Inorganic iron oxides	10 mg/m3	NE	10 mg/m3	NE
Chromium III trivalent chromium	.5 mg/m3	NE	.5 mg/m3	NE

ENGINEERING CONTROLS Use local exhaust ventilation to maintain airborne concentrations below exposure limits. Respiratory protection may be required in addition to general room ventilation.

PERSONAL PROTECTIVE EQUIPMENT Use a properly fitted, air-purifying or air supplied respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

EYE PROTECTION Eye protection such as chemical splash goggles and/or face shield must be worn when possibility exists for eye contact due to splashing or spraying liquid, airborne particles or vapor. Contact lenses should not be worn.

SKIN AND BODY PROTECTION When skin contact is possible, protective clothing including gloves, apron, sleeves, boots, head and face protection should be worn. Gloves should be impervious neoprene or rubber. Use of barrier cream is recommended. Clean equipment thoroughly after each use. Discard contaminated leather shoes and canvas sneakers.

OTHER HYGENIC PRACTICES Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

OTHER WORK PRACTICES Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet facilities. Promptly remove soiled clothing and wash thoroughly before reuse. Shower after work using plenty of soap and water.

SECTION 9 Physical and Chemical Properties

Appearance	
Form	Viscous Liquid
Color	varies
pH	Not available
Melting/Freezing Temperature	40 C/ 104 F
Boiling Point	336 C/ 637 F
Flash Point	485 F
Ignition Temperature	Not available
Autoignition Temperature	Not available
Lower explosive limit; na	Upper explosive limit: na
Vapor Pressure	Not Available
Vapor Density (air=1)	Not available
Specific Gravity (water=1 @39.2F)	1.55
Evaporation Rate (Bac=1)	None
Odor	mild
Odor threshold	Not available

SECTION 10 Stability and Reactivity

Chemical Stability

Stable under recommended storage conditions

Possibility of Hazardous Reactions

No data available

Conditions to Avoid

Avoid strong acids, bases in bulk and elevated temperatures

Materials to Avoid

Reactive or incompatible with: acids, oxidizers, amines

Hazardous Decomposition Products

Decomposition products formed under fire conditions may include: Carbon oxides, Nitrogen oxides, Aldehydes.

SECTION 11 Toxicological Information

Acute Toxicity

Oral LD50	Rat > 4000 mg/kg.
Dermal LD50	Rabbit 20,000 mg/kg
Inhalation LC50	No data available

Carcinogenicity

IARC: No component of this product presents at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC

Skin Corrosion/Irritation

Skin	Irritant
------	----------

ACGIH: No component of this product presents at levels greater than or equal to 0.1% is identified as carcinogen or potential carcinogen by ACGIH

Serious Eye Damage/Eye Irritation

Eye	Irritant
Eyes	Rabbit
Severe eye irritation – 24 H	

NTP: No component of this product presents at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP

Respiratory or Skin Sensitization

May cause skin or respiratory sensitization

Mutagenicity

Mouse	Skin
Carcinogenic by RTECS Criteria	
liver, ovarian, thyroid	

SECTION 12 Ecological Information

Aquatic Ecotoxicity

No data available

Biodegradability

Persistent	Not readily biodegradable
------------	---------------------------

Mobility in soil

No data available

SECTION 13 Disposal Considerations

Waste Disposal

The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residuals. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

