## L20/480 HINGED HYGIENIC GRP DOOR SETS

## **Dortek K Type Hinged Door Sets**

Manufacturer: Dortek Ltd St Mark Street Hull HU8 7ED United Kingdom

Door : The doors shall be seamless glass-fibre reinforced polyester moulded

around non-organic hi-density closed cell core.

Reference : Dortek Type K Single action or Pair – Single action

Sizes : See list of manufacturers standard sizes.

Core : High density closed cell C.F.C and HFC free. Thermal conductivity 0.50 W/m sq. : Seamless hygienic moulded polyester, 2.5mm thick. Moisture absorption zero.

Door leaf : 40mm thick.

Finish : Smooth non-porous gelcoat finish with built in colour

Colour : Standard Super White 337 or choice of 20 colours see chart or RAL / BS to order

Colour is integrated into door skin (no decoration required)

Door frame : Seamless GRP or Steel profile frame or Aluminium profile frame to suit wall

thickness finish Stainless or PPC or Anodised (aluminium)

steel or powder coated or anodised aluminium to suit wall thickness.

Specify wall thickness

Hinges : Stainless steel lift off (standard or highload) – Non lift off available

Glazing Double glazed with laminate safety glass or acrylic finished flush with both

faces of door. Size 200 x 300mm or 200 x 600mm or 300 x 600mm or 400 x 600mm

positioned 165mm from leading edge or other sizes on request

Protection : 3mm thick ribbed rubber standard colour grey, or 2mm thick smooth

finish high impact grey PVC or 0.7mm thick stainless steel, bonded to door leaf or black polypropylene bumpers 250mm deep or 480mm deep

Fixing : Fix direct to structure with stainless steel screws.