

---

## L20/480 SLIDING HYGIENIC GRP DOORSETS

### Dortek K Type Single Sliding Door Sets

Manufacturer : Dortek Ltd St Mark Street Hull HU8 7ED United Kingdom

- Door : The doors shall be seamless glass-fibre reinforced polyester moulded around non-organic hi-density closed cell core. Doors wider than 1125mm will have a hygienic gel coat vertical joint.
- Reference : Dortek Type K Single - S-SL sliding door *or* - HS-SL sliding door
- Sizes : *See list of manufacturers standard sizes*
- Core : High density closed cell C.F.C and H.F.C free thermal conductivity 0.05 W/m sq
- Facing : Seamless hygienic moulded polyester, 2.5mm thick. moisture absorption zero.
- Door leaf : 40mm thick.
- Finish : Smooth non-porous gelcoat finish with built in colour
- Colour : Standard Super White 336 *or choice of 20 colours see chart or* RAL / BS *to order.*
- Door frame : Anodised aluminium angle *or* steel profile to suit wall thickness finish stainless steel *or powder coated* *or* anodised aluminium to suit wall thickness *specify wall thickness*
- Ironmongery : Stainless steel flush & pull handles. *Specify. Locks etc*
- Track : Aluminium rail system with nylon bearings
- Guide : Internal bottom track with nylon guide
- Glazing : Triple glazed with laminate safety glass *or* polycarbonate outer panes finished flush with both faces of door Size 200 x 300mm *or* 200 x 600mm *or* 300 x 600mm *or* 400 x 600mm position 165mm from leading edge *or other sizes on request*
- Canopy : White coated *or* Stainless steel with sloping top.
- Operation : Manual (Not self closing) *or* Electrical automation micro processor controlled with safety photo-cell, in-built safety sensor to open the door if obstructed operated with 2 push buttons *or* 2 touchless sensors *or* 2 infra red detectors. *Specify* Battery back up to operate door in case of power failure